

# Bro User Manual

---

version 0.9, 12-1-2004, **DRAFT**

Vern Paxson, Jim Rothfuss, Brian Tierney

Contact: [vern@icir.org](mailto:vern@icir.org)

<http://www.bro-ids.org/>

---

This the User Manual for Bro version 0.9.

This software is copyright © (add copyright here)

For further information about this notice, contact:

Vern Paxson email: [vern@icir.org](mailto:vern@icir.org)

# Table of Contents

<b>1</b>	<b>Overview of Bro .....</b>	<b>2</b>
1.1	What is Bro? .....	2
1.2	Bro features and benefits.....	2
1.3	Getting more Information.....	3
<b>2</b>	<b>Requirements.....</b>	<b>5</b>
2.1	Network Tap.....	5
2.2	Hardware and Software Requirements.....	5
<b>3</b>	<b>Installation and Configuration .....</b>	<b>8</b>
3.1	Download.....	8
3.2	Install.....	8
3.3	Bro Configuration.....	9
3.4	OS Configuration.....	11
3.5	Encrypted Reports.....	11
3.6	Generating Reports on a Separate Host.....	12
3.7	Web GUI Installation / Configuration.....	13
<b>4</b>	<b>Running Bro .....</b>	<b>14</b>
4.1	Starting Bro.....	14
4.2	Bro Scripts.....	14
4.3	Sending (E-mail) Bro Reports.....	15
4.4	Reading a Bro Report.....	15
4.4.1	Parts of a Report.....	15
4.4.2	Annotated Example Report:.....	17
<b>5</b>	<b>Analysis of Incidents and Alarms .....</b>	<b>26</b>
5.1	Two Types of Triggers.....	26
5.1.1	Converted Signatures.....	26
5.1.2	Embedded Bro Rule.....	26
5.2	General Process Steps.....	27
5.3	Understand What Triggered the Alarm(s).....	27
5.3.1	Converted Snort Signatures.....	27
5.3.2	Embedded Bro Rule.....	28
5.4	Understand the Intent of the Alarm(s).....	29
5.4.1	Converted Snort© Signatures.....	29
5.4.2	Embedded Bro Rule.....	30
5.5	Examine HTTP FTP or SMTP Sessions.....	30
5.6	Examine the Connection and Weird Logs.....	31
5.6.1	Breakin Indicators.....	31
5.6.2	Connections to Other Computers.....	31
5.6.3	Odd Activity.....	32

5.7	Examine the Bulk Trace if Available .....	32
5.8	Contact and Question Appropriate People .....	32
<b>6</b>	<b>Customizing Bro .....</b>	<b>33</b>
6.1	Policy Files .....	33
6.2	Notices .....	34
6.3	Notice Actions .....	37
6.4	Signatures .....	38
6.4.1	Turning Signatures ON/OFF .....	38
6.4.2	Add a New Signature .....	39
6.4.3	Editing Existing Signatures .....	39
6.4.4	Importing Snort Signatures .....	39
6.4.5	Checking for new Signatures from bro-ids.org .....	39
6.5	Tuning Scan Detection .....	39
6.6	Other Customizations .....	40
<b>7</b>	<b>Intrusion Prevention Using Bro .....</b>	<b>42</b>
7.1	Terminating a connection .....	42
7.2	Updating Router ACL .....	42
<b>8</b>	<b>Performance Tuning .....</b>	<b>43</b>
8.1	Hardware and OS Tuning .....	43
8.2	Bro Policy Tuning .....	44
<b>9</b>	<b>Bulk Traces and Off-line Analysis .....</b>	<b>45</b>
9.1	Bulk Traces .....	45
9.2	Off-line Analysis .....	45
<b>Appendix A</b>	<b>Bro Directory and Files .....</b>	<b>47</b>
A.1	The bro/bin Directory .....	47
A.2	The bro/etc Directory .....	48
A.3	The bro/var Directory .....	49
A.4	The bro/scripts Directory .....	49
A.5	The bro/policy Directory .....	50
A.6	The bro/site Directory .....	54
A.7	The bro/logs Directory .....	54
A.8	The bro/archive Directory .....	56
A.9	Other Files .....	56
<b>Index</b>	<b>.....</b>	<b>57</b>

**Bro User Manual**

# 1 Overview of Bro

## 1.1 What is Bro?

Bro is a Unix-based Network Intrusion Detection System (IDS). Bro monitors network traffic and detects intrusion attempts based on the traffic characteristics and content. Bro detects intrusions by passing network traffic through rules describing events that are deemed troublesome. These rules might describe activities (e.g., certain hosts connecting to certain services), what activities are worth alarming (e.g., attempts to a given number of different hosts constitutes a "scan"), or signatures describing known attacks or access to known vulnerabilities. If Bro detects something of interest, it can be instructed to either issue a log entry or initiate the execution of an operating system command (such as sending email, or creating a router entry to block an address).

Bro targets high-speed (Gbit/second), high-volume intrusion detection. By judiciously leveraging packet filtering techniques, Bro is able to achieve the performance necessary to do so while running on commercially available PC hardware, and thus can serve as a cost effective means of monitoring a site's Internet connection.

## 1.2 Bro features and benefits

- **Network Based**

Bro is a network-based IDS. It collects, filters, and analyzes traffic that passes through a specific network location. A single Bro monitor, strategically placed at a key network junction, can be used to monitor all incoming and outgoing traffic for the entire site. Bro does not use or require installation of client software on each individual, networked computer.

- **Custom Scripting Language**

Bro policy scripts are programs written in the Bro language. They contain the "rules" that describe what sorts of activities are deemed troublesome. They analyze the network activity and initiate actions based on the analysis. Although the Bro language takes some time and effort to learn, once mastered, the Bro user can write or modify Bro policies to detect and notify or alarm on virtually any type of network activity.

- **Pre-written Policy Scripts**

Bro comes with a rich set of policy scripts designed to detect the most common Internet attacks while limiting the number of false positives, i.e., alarms that confuse uninteresting activity with the important attack activity. These supplied policy scripts will run "out of the box" and do not require knowledge of the Bro language or policy script mechanics.

- **Powerful Signature Matching Facility**

Bro policies incorporate a signature matching facility that looks for specific traffic content. For Bro, these signatures are expressed as regular expressions, rather than fixed strings. Bro adds a great deal of power to its signature-matching capability because of its rich language. This allows Bro to not only examine the network content, but to understand the context of the signature, greatly reducing the number of false positives. Bro

comes with a set of high-value signatures, selected for their high detection and low false positive characteristics, as well as policy scripts that perform more detailed analysis.

- **Network Traffic Analysis**

Bro not only looks for signatures, but also analyzes network protocols, connections, transactions, data volumes, and many other network characteristics. It has powerful facilities for storing information about past activity and incorporating it into analyses of new activity.

- **Detection Followed by Action**

Bro policy scripts can generate output files recording the activity seen on the network (including normal, non-attack activity). They can also send alarms to event logs, including the operating system *syslog* facility. In addition, scripts can execute programs, which can, in turn, send e-mail messages, page the on-call staff, automatically terminate existing connections, or, with appropriate additional software, insert access control blocks into a router's access control list. With Bro's ability to execute programs at the operating system level, the actions that Bro can initiate are only limited by the computer and network capabilities that support Bro.

- **Snort Compatibility Support**

The Bro distribution includes a tool, *snort2bro*, which converts Snort signatures into Bro signatures. Along with translating the format of the signatures, *snort2bro* also incorporates a large number of enhancements to the standard set of Snort signatures to take advantage of Bro's additional contextual power and reduce false positives.

## 1.3 Getting more Information

- **Reference manual**

An extensive [reference manual](#) is provided detailing the Bro Policy Language

- **FAQ**

Several Frequently Asked Questions are outlined in the [Bro FAQ](#). If you have a question not already covered in the FAQ, send it to us and we'll add it.

- **Tutorial**

Over a hundred [tutorial viewgraphs](#) covering every aspect of Bro set up and use.

- **E-mail list**

Send questions on any Bro subject to [bro@bro-ids.org](mailto:bro@bro-ids.org) The list is frequented by all of the Bro developers.

You can subscribe by going to the website:

<http://bro-ids.org/mailman/listinfo/bro>,

or by placing the following command in either the subject or the body of a message addressed to [bro-request@bro-ids.org](mailto:bro-request@bro-ids.org).

```
subscribe [password] [digest-option] [address=<address>]
```

A password must be given to unsubscribe or change your options. Once subscribed to the list, you'll be reminded of your password periodically. The "digest-option" may be either: "nodigest" or "digest" (no quotes!). If you wish to subscribe an address other than the address you use to send this request from, you may specify "address=<email address>" (no brackets around the email address, no quotes!)

- **Website**

The official Bro website is located at: <http://www.bro-ids.org>. It contains all of the above documentation and more.



## 2 Requirements

### 2.1 Network Tap

Bro requires a network tap to give it access to live network traffic. The tap needs to be full-speed for the link being monitored and must provide copies of both directions of the link, or you need to two taps, one in each direction.

Normally the network tap for Bro should be placed behind an external firewall and on the DMZ (the portion of the network under the control of the organization but outside of the internal firewall), as shown in the figure below. Some organizations might prefer to install the network tap outside the firewall in order to detect all scans or attacks. Placing Bro outside the firewall will allow the organization to better understand attacks, but will produce a more notifications and alarms. Another option is to place Bro inside the internal firewall, allowing it to detect internal hosts with viruses or worms. In addition to the connection to the network tap, a separate network connection is recommended for management of Bro and access to log files.

For more information on taps and tap placement see the Netoptics White paper titled *Deploying Network Taps with Intrusion Detection Systems* (<http://www.netoptics.com/products/pdf/Taps-and-IDSs.pdf>).




Figure 2.1: Typical location for network tap and Bro system

### 2.2 Hardware and Software Requirements

Bro requires no custom hardware, and runs on low-cost commodity PC-style systems. However, the Bro monitoring host must examine every packet into and out of your site, so depending on your site's network traffic, you may need a fairly high-end machine. If you are trying to monitor a link with a large number of connections, we recommend using a second system for report generation, and run only Bro on the packet-capture host.

Item	Requirements
------	--------------

<b>Processor</b>	<p>Note: these are <b>rough</b> estimates. Much depends on the number of connections/second, the types of traffic on your network (e.g., HTTP, FTP, email, etc.), and you can trade off depth of analysis (especially, which protocols are analyzed) for processing load. (See the Performance chapter of the Bro User Guide for more information.)</p> <p>1 GHz CPU for 100 Mbps monitoring with average packet rate <math>\leq</math> 5,000 packets/second</p> <p>2 GHz CPU for 1 Gbps monitoring with <math>\leq</math> 10,000 packets/second</p> <p>3 GHz CPU for 1 Gbps monitoring with <math>\leq</math> 20,000 packets/second</p> <p>4 GHz CPU for 1 Gbps monitoring with <math>\leq</math> 50,000 packets/second</p>
<b>Operating System</b>	<p>Recommended: FreeBSD (<a href="http://www.freebsd.org/">http://www.freebsd.org/</a>). Bro works with many Unix systems, including Linux and Solaris, but has been primarily tuned for FreeBSD. We recommend using FreeBSD version 4.10 for Bro. If your site has a large number of packets or connections per second you should look at the section on <a href="#">Section 8.1 [Hardware and OS Tuning]</a>, page 43. FreeBSD 5.x should work, but has not been tested by the developers. For sites with very high traffic loads, contact us for a FreeBSD 4.x kernel patch to do <i>BPF bonding</i>, which allows merging the two directions of a network link into a single interface as seen by Bro. While Bro can instead merge the two interfaces at user-level, this costs some performance.</p>
<b>Memory</b>	<p>512 MB suffices for small networks (say 200 hosts connected via a 100 Mbps link). For larger networks, 1 GB RAM will be required, with 2-3 GB is recommended.</p>
<b>Hard disk</b>	<p>10 GB minimum, 50 GB or more for log files recommended.</p>
<b>User privileges</b>	<p><i>superuser</i> to install Bro, with Bro then running as user <i>bro</i>.</p>
<b>Network Interfaces</b>	<p>3 interfaces are recommended: 2 for packet capture (1 for each direction), and 1 for host management. Capture interfaces should be identical. For some network taps, both directions of the link are captured using the same interface, and the separate host management interface, while prudent, is not required.</p>

**Other Software**

- Perl version 5.6 or higher (<http://www.perl.org>) (for report generation)

- libpcap version 0.7.2 or higher (<http://www.tcpdump.org>)

Note: Some version of FreeBSD come with older versions of libpcap. Bro recommends newer versions of these tools for performance reasons.

- Apache 1.3 http server (<http://httpd.apache.org>) (for Bro GUI)

- Python version 2.3 or higher (<http://www.python.org>) (for Bro GUI)

## 3 Installation and Configuration

### 3.1 Download

Download Bro from: <http://www.bro-ids.org/>

You can unpack the distribution anywhere except into the directory you plan to install into. To untar the file, type:

```
tar xzf bro-pub-0.9-current.tar.gz
```

### 3.2 Install

You'll need to collect the following information before beginning the installation.

- localnets: a list of local subnets for your network. Bro needs to know which networks are "internal" and which are "external".
- interface names: the names of the capture interfaces in your host (e.g. sk0 or en1). Use `ifconfig -a` to get the list of all network interfaces on your Bro host.

If you want to use Bro's periodic email report feature, you'll also need:

- email list: a list of email addresses to send the reports to.
- PGP keys: if you want to encrypt all email reports, the location of the **GPG keyring** of all recipients.

Bro is easy to install. Log in as `root`, and type:

```
./configure
```

or to install Bro in a location other than `'/usr/local/bro'`, use:

```
./configure --prefix=/path/to/bro
```

and then type:

```
make
make install
```

or

```
make install-brolite
```

Use *make install* to install all the Bro binaries and policy script files. Use *make install-brolite* to also run the configuration script (described in the next section) and installs all the configuration files and `cron` jobs.

To update an existing Bro installation with new binaries and standard policy files, instead of "make install" do a "make update". This will preserve all your local customizations.

Also note that this documentation is installed in `BROHOME/docs` as both HTML and PDF versions.

### 3.3 Bro Configuration

The *Bro-Lite* configuration script can be used to automatically configure (or reconfigure) Bro for you. It checks your system's BPF settings, creates a "bro" user account, installs a script to start Bro at boot time, and installs a number of `cron` jobs to checkpoint Bro every night, run periodic reports, and manage log files.

To run this configuration script type:

```
bro_config
```

This script creates the file '\$BROHOME/etc/bro.cfg'. `bro_config` will ask a number of simple questions.

Sample output of `bro_config`, along with explanation, is shown below:

```
Running Bro Configuration Utility
Checking interfaces .... Done.
Reading /usr/local/bro/etc/bro.cfg.example for defaults.

    The bro_config script looks first at ./bro.cfg, then
    /usr/local/bro/etc, for default values to use below.

Bro Log archive location [/usr/local/bro/archive]

    This is the directory where log file archives are kept.
    If you expect the log files to be very large, it is recom-
    mended to put these in a separate disk partition.

User id to install and run Bro under [bro]

    bro_config will create a new user account with this
    username if the user does not exist.

Interface names to listen on. [en1,en2]

    bro_config looks for all network interfaces and does a
    short test to determine which interfaces see the most
    traffic, and selects these interfaces as the default.

Site name for reports (i.e. LBNL, FOO.COM, BAZ.ORG) []
Starting Report Time [0600]
Report interval (in hours) [24]
Email addresses for internal reports [bro@localhost]
Do you want to send external reports to a incident
    reporting org (e.g.: CERT, CIAC, etc) (Y/N)
Y
Email addresses for external reports []

    Daily reports will be created. Enter the site name you
    want to appear at the top and in the subject of all
    email reports. The "start time" and "interval" define
    the window of network activity that the daily report
    will cover, starting at "Starting Report Time" and last-
    ing through "Report interval". The start time should
    be entered using 24hr clock notation. For example:
    12:30AM = 0030, 2PM = 1400
```

Two types of reports will be generated, "internal" and "external". Internal reports contain the same basic information as the external reports, along with traffic statistics and more detailed information on incidents. Both internal and external reports will be sent to the "internal" email address list. External reports are only sent if you answer "Y" and enter an external email address. (Note: currently only internal reports are generated)

Do you want to encrypt the email reports (Y/N) [N]

Y

If you want the email reports encrypted, you will need to set up GPG (<http://www.gnupg.org>) and create a GPG keyring containing the public keys of all email recipients. Instructions for this are in [Section 3.5 \[Encrypted Reports\]](#), page 11. *Note: PGP keys are compatible with GPG, but the Bro supplied scripts require GPG, not PGP.*

Running script to determine your local subnets ...

Your Local subnets [198.129.224.1/32]

Bro needs to know a list of your local subnets. `bro_config` runs a tool that attempts to discover this automatically. You should always verify the results of this tool. The format is a list of subnet/significant bits of address. For example: 131.243.0.0/16, 198.128.0.0/18, 198.129.224.1/32 This information will be stored in the file `$BROHOME/site/local.site.bro`

Saving settings to file: `/usr/local/bro/etc/bro.cfg`

Bro configuration finished.

To change these values, you can rerun `bro_config` at any time.

Indicates that the script finished successfully.

For site monitoring very high traffic rates on Gigabit Ethernet, there is some additional system tuning that should be done. See the [Chapter 8 \[Performance Tuning\]](#), page 43 section for more details.

To reconfigure Bro, run:

```
BRHOME/scripts/bro_config
```

This will update your `/usr/local/bro/etc/bro.cfg` file. You can also edit this file using your favorite editor if you prefer.

For other site customizations, you can edit the file `$BROHOME/site/local.site.bro`. For example, to tell bro to not look at traffic for host 198.162.44.66, add:

```
redef restrict_filters += {
  ["ignore host 198.162.44.66 "] =
    "not host 198.162.44.66"
};
```

More details are available in the section on [Chapter 6 \[Customizing Bro\]](#), page 33.

### 3.4 OS Configuration

This section contains information on critical OS tuning items. More detailed tuning information can be found in the section on [Chapter 8 \[Performance Tuning\]](#), page 43.

#### FreeBSD Configuration

The standard FreeBSD 4.10 kernel imposes a per-process limit of 512 MB of memory. This is not enough for most Bro installations. Unfortunately the only way to increase this limit is to rebuild the kernel.

To check your current limit, type:

```
limits -H
```

and look at the `datasize` setting, which should be the same as your amount of RAM. If this is not true, see section [Section 8.1 \[Hardware and OS Tuning\]](#), page 43 for information on fixing this.

#### Linux Configuration

increase these (need to get recommended values for these):

```
/proc/sys/net/core/rmem_default (IP-Stack socket receive queue)
/proc/sys/net/core/rmem_max      (similar to rmem_default)
/proc/sys/net/core/netdev_max_backlog (queue between driver and socket)
```

### 3.5 Encrypted Reports

Bro can use GPG (<http://www.gnupg.org/>) to encrypt the reports that it sends. To have Bro encrypt your reports you must have said "yes" to the `bro-config` question to encrypt your reports. Then each email recipient must generate a public/private key pair, and their public key must be installed on the Bro machine in the home directory of the user running the Bro process.

To create a key-pair:

```
gpg --gen-key
```

To export the public key:

```
gpg --armor --output mykey.gpg --export myemail@address.com
```

Then login to the machine running Bro and import the list of public keys:

```
gpg --import mykey.gpg
```

Then you must make the list of keys "trusted" so that they can be used to encrypt the email reports. To do this, you must edit the key to add "ultimate" trust to the key.

```
gpg --edit-key myemail@address.com
```

```
pub 1024D/4A872E40  created: 2001-02-05 expires: never      trust: -/f
sub 3072g/B72DD7FE  created: 2001-02-05 expires: never
(1). Some R. User <myemail@address.com>
```

```
Command> trust
```

```
pub 1024D/4A872E40  created: 2001-02-05 expires: never      trust: -/f
sub 3072g/B72DD7FE  created: 2001-02-05 expires: never
(1). Some R. User <myemail@address.com>
```

```

Please decide how far you trust this user to correctly
verify other users' keys (by looking at passports,
checking fingerprints from different sources...)?

 1 = Don't know
 2 = I do NOT trust
 3 = I trust marginally
 4 = I trust fully
 5 = I trust ultimately
 m = back to the main menu

Your decision? 5
Do you really want to set this key to ultimate trust? yes

pub 1024D/4A872E40  created: 2001-02-05 expires: never      trust: u/u
sub 3072g/B72DD7FE  created: 2001-02-05 expires: never
(1). Some R. User <myemail@address.com>

Command> quit

```

For more information on GPG see <http://www.gnupg.org/>

### 3.6 Generating Reports on a Separate Host

*Warning: this section assumes a reasonably high level of Unix system administration skills!*

If your site has lots of traffic, lots of connections, or if Bro is using on average more than around 40% of your CPU, you'll want to use a second host for generating reports.

To do this, on the Bro host, run `bro-config`, and say "N" to all report generation questions. Then install Bro on the second host using the following:

```

./configure
make
make install-reports

```

Then follow the instructions in [Section 3.3 \[Bro Configuration\]](#), page 9 for setting up report generation.

You'll also need to set up a method to copy files from the Bro host to the report generation host. One way to do this is using `rsync`, and the Bro script `push_logs.sh` does this for you. For example, you can set up a cron job like this on the Bro host:

```
1 1 * * * (push_logs.sh /usr/local/bro/etc/bro.cfg host:/home/bro) >> /tmp/bro-push.log
```

To make sure your `rsync` command has time to transfer all log files before your report generation script is run, the `push_logs.sh` script is designed to be used with the scripts `frontend-site-report.sh` and `frontend-mail-report.sh` on the frontend host. These `frontend` scripts wait for a file with a particular name to exist before running. It is also important to use the `nice` command to help ensure the network copy does not unduly divert processing away from Bro.



You may want to `rsync` the log files over a secure ssh connection. To do this, you need to first generate a ssh key pair on the Bro capture host with no passphrase:

```
ssh-keygen -t rsa -C "batch key" -f ./batch.key
```

Put this in user `bro`'s `.ssh/config` file, also on the Bro capture host

```
Host recvhost brohost.foo.com
IdentityFile ~/.ssh/batch.key
```

On the frontend host where the log files will be processed, add `batch.pub` to the `authorized_keys` file

```
cat batch.key.pub >> authorized_keys
```

Then create a cron entry on the Bro capture host

```
1 1 * * * nice -n 20 rsync -e 'ssh' -azv \
/usr/local/bro/logs host:/home/bro
```

### 3.7 Web GUI Installation / Configuration

The Bro Web Logfile viewing GUI is not yet packaged in an easy to install format. However if you want to give try installing it, there are instructions at: <http://www.icir.org/twiki/bin/view/Bro/BrooeryGUI/>

This web GUI can run on a lightly loaded Bro host, but it is recommended to run this on a separate host. Use the `rsync` method described in [Section 3.6 \[Generating Reports on a Separate Host\]](#), [page 12](#) to copy files to the web host. Note: this web server should NOT be publicly accessible to the Internet. Information in the log files is generally very sensitive.

## 4 Running Bro

### 4.1 Starting Bro

Bro is automatically started at boot time via the `bro.rc` script (located in `'$BROHOME/etc'` and `'/usr/local/etc/rc.d'` on FreeBSD, or `'/usr/init.d'` on Linux).

To run this script by hand, type:

```
bro.rc start
```

or

```
bro.rc checkpoint
```

or

```
bro.rc stop
```

Use `checkpoint` to restart a running Bro, loading a new policy file.

### 4.2 Bro Scripts

Installing Bro automatically creates the following `cron` jobs, which are run on at the specified intervals.

- `site-report.pl`: generates an email report of all alarms and notifications
- `mail_reports.sh`: send email reports

These scripts can also all be run by hand at any time.

As Bro log files can get large quickly, it is important to ensure that the Bro disk does not fill up. Bro includes some simple scripts to help manage disk space. Most sites will want to customize these for their own requirements, and integrate them into their backup system to make sure files are not removed before they are archived.

- `check_disk.sh`: send email if disk space is too low
- `bro_log_compress.sh`: remove/compress old log files

These scripts can be customized by editing their settings in `$BROHOME/etc/bro.cfg`. The settings are as follows:

- `check_disk.sh`:
  - `diskspace_pct`: when disk is  $\geq$  this percent full, send email (default = 85%)
  - `diskspace_watcher`: list of email addresses to send mail to
- `bro_log_compress.sh`:
  - `Days2deletion`: remove files more than this many days old (default = 60)
  - `Days2compression`: compress files more than this many days old (default = 30)

## 4.3 Sending (E-mail) Bro Reports

A daily "internal" report is created that covers three sets of information:

- Incident information
- Operational status of Bro
- General network traffic information

If the local organization is asked to report incidents to another incident analysis organization (e.g., CERT, CIAC, or FedCIRC) an auxiliary "external" report can be created that only contains the incident information. These reports are stored in `$BRODIR/reports`.

The two reports will be mailed to the email addresses specified during Bro installation. These email addresses can be changed by re-running the `bro_config` script or by editing `$BROHOME/etc/bro.cfg` directly. Each report has its own set of email addresses. If it is desired to send the auxiliary report directly to the external incident analysis organization without inspection, enter their email address directly. Otherwise, have the external email sent to someone who can inspect and forward it appropriately.

## 4.4 Reading a Bro Report

The report is divided into three parts, the summary, incidents, and scans. The summary includes a rollup of incident information, Bro operational statistics, and network information. The incidents section has details for each Bro alarm. The scans section gives details about scans that Bro detected.

### 4.4.1 Parts of a Report

#### Header

The header gives some basic information about the report.

**Site name** is determined by the "Site name for reports" that was given during the installation and configuration process.

**Start time and interval** of the report are also entered during the configuration process.

See [Section 3.3 \[Bro Configuration\]](#), page 9.

#### Summary

This section give a numeric summary of the events that have happened in the reporting period.

**Incidents** shows the number of incidents that are recorded in the report period. An incident is any occurrence that is deemed worth investigating. An incident is formed by the triggering of one or more alarms.

**Scanning Hosts** are the number of specific IP addresses that have been detected scanning either into or out from the site.

**A scan can be a:**

- **port scan:** scanning several ports of a single host.
- **network scan:** scanning several hosts for open ports.
- **signature scan:** attacking multiple hosts with a specific vulnerability attack (signature).
- **targeted attack:** launching multiple signatures against a single host.
- **password scan:** attempts to guess passwords on telnet terminals.

**A successful scan is when:**

- the bytes sent by a single probe of a scan against a host or several hosts are more than three deviations away from the standard deviation of the rest of scan. In essence, where the bytes transferred on one connection is different than the rest of the scan other connections involved in the scan.
- a separate connection back to the attacker host is detected from the local network.
- the number of bytes sent back from the targeted victim host to the offender during a scan connection exceeds 20480.

**Signature Summary** shows the total number of alarms triggered by signatures during the report period and the number of those that are unique. These numbers do not include alarms triggered by embedded Bro rules. See [Section 5.3 \[Understand What Triggered the Alarm\(s\)\]](#), page 27.

## Signature Distributions

This is a list of all signatures that were triggered during the report period.

NOTE: This section does not include alarms triggered by embedded Bro rules. See [Section 5.3 \[Understand What Triggered the Alarm\(s\)\]](#), page 27.

**Count** is the number of times the signature was seen.

**Unique Sources** is the number of unique ip addresses that used the specific signature as an attack.

**Unique Dests** is the number of unique ip addresses that were attacked by the particular signature.

**Unique Pairs** are the number of unique source/dest ip address pairs where the source used the signature to attack the destination.

## Incidents

**Legend:** This is the legend for reading the *connections* portions of the each incident. It is shown once on each report at the top of the *Incidents* section.

**Incident number:** Each incident listed in the Bro report is assigned a unique, sequential, identification number prefixed with the organization identifier. This number is unique for all incidents, not just to the daily reports.

**Remote and Local hosts:** The Remote and Local hosts are identified by both ip address and hostname. The local hosts are those that are in local subnets as determined during Bro configuration. It is important to note that *remote host* does not infer *attack host*. Attacks can come from local hosts (indicating an inside hacker or a compromised host).

**Alarms:** The network event(s) that Bro detects and identifies as possible attacks. There are two general types of alarms, those triggered by signatures and those triggered by Bro rules. See [Section 5.3 \[Understand What Triggered the Alarm\(s\)\]](#), page 27, for more information about the differences. All alarms will include the date/time of the attack, the direction of the attack, and the ports involved. A **SensitiveSignature** will include the signature code and payload to help evaluate what triggered the alarm. Embedded Bro rules will include the payload and a session number which can be used for further investigation in the logs. See [Section 5.5 \[Examine HTTP FTP or SMTP Sessions\]](#), page 30.

**Connections:** A list of the first 25 connections after the first alarm is triggered that are attempted between the attacking and victim host. This tabulation of connections can be used to see if connections were accepted by the victim host, the amount of bytes transferred in both directions, the timing between the connections, and the ports involved.

## Scans

This is a summary of the ip addresses involved in successful scans, the type of scans, and the attacks used by the scanners.

## Connection Log Summary

This section gives an overview of the most prominent connections that have occurred during the report period, as shown by way of five tables.

**Site-wide connection statistics:** The number of successful and unsuccessful connections and the ratio between the two.

**Top 20 Sources:** Hosts that have initiated the most connections.

**Top 20 Destinations:** Hosts that have accepted connections.

**Top 20 Local E-mail Servers:** The most active E-mail servers.

**Top 20 Services:** The services, as determined by port number, that have been involved in connections.

## Byte Transfer Pairs

This section gives a summary of the ip address address pairs that have transferred the most bytes during the report period.

### 4.4.2 Annotated Example Report:

```
Site Report for ORG_NAME
from 2004/11/03 00:00:00 to 2004/11/04 00:00:00
generated on Sat Nov 13 12:02:48 2004
```

**annotation:** *ORG\_NAME* will normally be replaced with "Site name for reports" that was given during the installation and configuration process.

```
=====
Summary
=====
```

**annotation:** *Since this report is simple and only includes two incidents, the summary is rather uninteresting. A glance at this summary would reveal a rather "slow" day (for which you should be thankful).*

Incidents 2

Scanning Hosts

    Successful 8

    Unsuccessful 15

Signature Summary

    Total signatures 2

    Unique signatures 2

    Unique sources 2

    Unique destinations 2

    Unique source/dest pairs 1

**annotation:** *Since the same to ip addresses were involved in both signature attacks, there is only one unique source/dest pair.*

```
=====
Signature Distributions
=====
```

Signature ID	Count	Unique Sources	Unique Dests	Unique Pairs
bro-687-5	1	1	1	1
bro-144-3	1	1	1	1

```
=====
Incident Details
=====
```

**annotation:** *The following legend appears once in every report at the top of the "Incidents" section*

# legend for connection type #

    C Connection Status

        # number corresponds to alarm triggered by the connection

        \* successful connection, otherwise unsuccessful.

    I Initiator of Connection

        > connection initiated by remote host

        < connection initiated by local host

```
-----
Incident       ORG_NAME-000004524
-----
```

**annotation:** *The host domain name "org-name.org" will normally be replaced by the local domain name. The IP addresses in this example have been synthesized from an imaginary range outside of the octal range. (We realize these*

*ip addresses cannot exist). In this example the ip ranges 124.333.0.0/24 and 132.257.0.0/24 are considered the local subnets.*

Remote Host: 84.136.338.21 p54877614.dip.hacker.net

Local Host: 124.333.183.162 pooroljoe.dhcp.org\_name.org

**annotation:** *This attacker was successful in using an SQL attack and then downloaded a "tool" using TFTP. Both of these were detected and created the following alarms.*

Alarm: SensitiveSignature

```
1    bro-687-5: MS-SQL xp_cmdshell - program execution
      7/29 12:43:31                                84.136.338.21 -> 124.333.183.62
                                                    566/tcp -> 1433/tcp
```

signature code:

```
signature bro-687-5 {
  ip-proto == tcp
  dst-port == 1433
  event "MS-SQL xp_cmdshell - program execution"
  tcp-state established,originator
  payload /.*[xX]\x00[pP]\x00_\x00[cC]\x00[mM]\x00[dD]\x00[sS]
  \x00[hH]\x00[eE]\x00[lL]\x00[lL]\x00/
}
```

payload: xp\_cmdshell 'echo.> c:\\temp\\bcp.cmd'

Alarm: SensitiveSignature

```
2    bro-1444-3: TFTP Get
      7/29 12:43:31                                84.136.338.21 -> 124.333.183.62
                                                    2318/udp -> 69/udp
```

signature code:

```
signature bro-1444-3 {
  ip-proto == udp
  dst-port == 69
  event "TFTP Get"
  payload /\x00\x01/
}
```

payload: Runtime.exe

**annotation:** *Looking at the "C" column below, the alarms are signified by "1" and "2", both occuring at 12:43:31. Since the attacks take place within one second, this is probably an automated attack. The remote host continues to connect to the victim host, using a different port each time to avoid detection. The large transfers from the local host to the remote host, subsequent to the alarmed attacks, signifies that the attack is probably successful.*

Connections (only first 25 after first alarm are listed)

```
-----
      time      byte  remote      local  byte
date   time duration transfer  port  C   I   port transfer protocol
-----
07/29 12:43:31      ?    566 b  4634 1   >  1433    467 b tcp/MSSQL
```

```

07/29 12:43:31      0      ? 2318 2 < 69      20 b udp/tftp
07/29 12:43:32    265.7      4 b 4638 * < 2318      3.0kb udp
07/29 12:48:56      ?      ? 4640 * > 2362      ? tcp
07/29 12:50:05      ?    11.4kb 4639 * < 3333      8.6kb tcp
07/29 12:53:00      0      ? 4684 * > 2362      ? tcp
07/29 12:53:07      ?      ? 4685 * > 2362      ? tcp
07/29 12:53:59      ?      ? 4689 * > 2362      ? tcp
07/29 12:54:14      6.1      0 4693 * < 2380     94.2kb tcp
07/29 12:54:21      .5     50 b 4694 * > 2381      0 tcp
07/29 12:54:23      .7      ? 4695 * < 2382      0 tcp
07/29 12:54:25      .5     51 b 4696 * > 2383      0 tcp
07/29 12:54:27      .5     61 b 4697 * > 2384      0 tcp
07/29 12:54:28      .7     39 b 4698 * > 2385      0 tcp
07/29 12:54:31      .5     41 b 4699 * > 2386      0 tcp
07/29 12:54:33      1.2    4.9 kb 4700 * > 2387      0 tcp
07/29 12:54:35     12.8   195.0 kb 4701 * < 2388      0 tcp
07/29 12:54:53      .2      ? 4703 * < 2390      0 tcp
07/29 12:54:54      .5     37 b 4704 * > 2391      0 tcp
07/29 12:54:56      3.4     23 b 4705 * > 2392      0 tcp
07/29 12:55:04     21.4   308.7 kb 4706 * > 2393      0 tcp
07/29 12:55:27     50.7      ? 4707 * > 2394      ? tcp
07/29 12:59:23      ?      ? 4775 * > 1433      ? tcp
07/29 12:59:25      ?      ? 4774 * > 3333      ? tcp

```

**annotation:** *The next Incident demonstrates alarms triggered by embedded rules, rather than signatures.*

---

```
Incident      ORG_NAME-000004525
```

---

```
Remote Host:  80.143.378.186      p508FB2BA.dip.t-dialin.net
Local Host:   128.333.181.191     lemonade.lbl.gov
```

**annotation:** *Since these alarms are triggered in the HTTP protocol, the actual trigger rules are found in the file 'bro/policy/http.bro'.*

```
Alarm: HTTP_SensitiveURI
11/13 11:36:05      80.143.378.186 -> 128.333.181.191
                        1560/tcp -> 80/tcp

session: %4672
payload: GET http://cn.edit.vip.cnb.yahoo.com/config/login?.redir_
        _from=PROFILES
```

```
Alarm: HTTP_SensitiveURI
11/13 11:53:54      80.143.378.186 -> 128.333.181.191
                        2434/tcp -> 80/tcp

session:%7386
payload: GET http://l10.login.scd.yahoo.com/config/login?.redir_f
        rom=PROFILES?&
```



**annotation:** *In the connections shown below, all connections are from the remote host to the local host, with no successful connections back. Also the payload above is seeking yahoo.com. Hence the likelihood is that this is not an attack.*

Connections (only first 25 after alarm are listed)

date	time	time duration	byte transfer	remote port	C	I	local port	byte transfer	protocol
11/13	11:36:05	1.109227	297	1560	*	>	80	1531	http
11/13	11:36:06	?	?	1560		>	80	?	http
11/13	11:41:51	0.843209	301	3175	*	>	80	1533	http
11/13	11:41:52	?	?	3175		>	80	?	http
11/13	11:47:37	2.562365	281	4701	*	>	80	1382	http
11/13	11:47:39	?	?	4701		>	80	?	http
11/13	11:53:53	0.694131	293	2434	*	>	80	1529	http
11/13	11:53:54	?	?	2434		>	80	?	http
11/13	11:59:23	0.685181	301	3975	*	>	80	1529	http
11/13	11:59:23	?	?	3975		>	80	?	http
11/13	12:04:53	1.054925	289	1700	*	>	80	1527	http
11/13	12:04:54	?	?	1700		>	80	?	http
11/13	12:11:56	2.579652	283	3442	*	>	80	1523	http
11/13	12:11:59	?	?	3442		>	80	?	http
11/13	12:18:08	1.046188	289	1083	*	>	80	1531	http
11/13	13:14:42	?	?	3282		>	80	?	http
11/13	13:16:46	?	?	4802		>	80	?	http
11/13	13:19:04	1.731771	0	2764	*	>	80	0	http
11/13	13:19:07	?	?	2764		>	80	?	http
11/13	13:20:42	0.994114	289	4142	*	>	80	1527	http
11/13	13:20:43	?	?	4142		>	80	?	http
11/13	13:22:37	1.122448	292	1732	*	>	80	1523	http
11/13	13:22:38	?	?	1732		>	80	?	http
11/13	13:24:40	1.042112	289	3179	*	>	80	1531	http
11/13	13:24:41	?	?	3179		>	80	?	http

Scans (only first 100 shown)

**annotation:** *The scans show below are considered "successful". Four interesting scans shown below are the ones originating from the 124.333 and 132.257 domains, since they are local domains. These should be investigated. The attack against 132.257.85.96 might also be investigated further. With each report, a review of the attacks will give an understanding of what types of scans are becoming "popular".*

Scanning IP	Victim IP	Attack
132.257.70.234	multiple	bro-1344-5
132.257.52.64	multiple	bro-1367-5

```

63.251.3.51      multiple      bro-2570-6
124.333.181.191 multiple      bro-1599-7
210.313.36.53   132.257.85.96 >1000 port scan
211.300.24.151  132.257.85.96 >1000 port scan
124.333.95.0    62.214.34.30  >250 port scan
172.278.206.135 multiple      (3128/tcp)

```

```

=====
Connection Log Summary
=====

```

**annotation:** *The connection log summary gives a general idea of what hosts are most active. The analyst may want to become familiar with any new hosts that appear on the next three lists and services that appear or radically change position on the fourth list*

Site-wide connection statistics

```

Successful:  4498748
Unsuccessful: 35941140
Ratio: 1:7.989

```

Top 20 Sources

Host	IP	Bytes	Conn. Count
-----	-----	-----	-----
ns1.org_name.org	124.333.34.186	3.7 G	683948
ns2.org_name.org	132.257.64.2	165 M	231245
lemonade.org_name.org	124.333.181.191	88 M	217781
nsx.org_name.org	132.257.64.3	371 M	200935
cinnamon.mining.com	207.5.380.138	4.5 M	103011
node2.lbnl.nodes.planet.org	198.328.56.12	106 M	75725
node1.lbnl.nodes.planet.org	198.328.56.11	85 M	73719
microscope.dhcp.org_name.org	132.257.19.79	61 M	54024
	169.299.224.1	2.3 M	40348
uhuru.org_name.org	132.257.10.97	423 M	39847
	132.257.77.246	13 M	29496
googledev.org_name.org	124.333.41.57	13 M	24930
	64.46.248.43	60 M	19785
...16-141.sfo4.dsl.contactor.net	66.292.16.141	6.2 M	19048
rock.es.net	198.128.2.83	2.8 G	18459
perry.Geo.college.EDU	124.32.349.11	1.7 M	17326
google.org_name.org	124.333.41.70	8.5 M	15508
egspd42212.search.com	65.264.38.212	3.1 M	15138
hmb-330-042.MSE.college.EDU	124.32.349.20	222 M	14865
1rodan.dhcp.org_name.org	132.257.19.170	7.7 M	11873

Top 20 Destinations

Host	IP	Bytes	Conn. Count
-----	-----	-----	-----

nsx.org_name.org	132.257.64.3	14 G	1571638
ns1.org_name.org	124.333.34.186	1.6 G	264976
ns2.org_name.org	132.257.64.2	80 M	218740
lemonade.org_name.org	124.333.181.191	2.6 G	176788
CS.university.EDU	128.312.136.10	10 M	81622
g.old-servers.net	192.42.293.30	11 G	71407
engram.CS.university.EDU	128.312.136.12	7.5 M	61309
aulvs.realthing.com	207.288.24.156	792 M	50493
ns1.college.EDU	124.32.349.9	995 M	39977
rohan.superc.gov	128.550.6.34	4.7 G	32883
sportsmed.starship.com	199.281.132.79	17 M	32152
ns2.yoho.com	66.263.169.170	2.1 G	24361
uhuru.org_name.org	132.257.10.97	58 M	19785
g3.NSDDD.COM	192.342.93.32	488 M	19734
w4.org_name.org	124.333.7.51	447 M	19334
E.TOP-SERVERS.NET	192.303.230.10	195 M	19066
mantis.org_name.org	124.333.7.39	395 M	18811
postala.org_name.org	124.333.41.61	8.0 M	17283
vista.org_name.org	132.257.48.146	488 M	15961
calmail.college.EDU	128.32.349.103	73 M	15154

## Top 20 Local Email Senders

Count	Hostname	IP	Conn.
-----	-----	-----	-----
	mta1.org_name.org	124.333.41.24	3869
	postala.org_name.org	124.333.41.61	2850
	ci.org_name.org	132.257.192.220	868
	postal2.org_name.org	132.257.248.26	376
	ee.org_name.org	132.257.1.10	173
	math.org_name.org	124.333.7.22	131
	rod2.org_name.org	132.257.112.183	121
	gigo.org_name.org	124.333.2.54	110
	mh1.org_name.org	124.333.7.48	82
	stm.org_name.org	132.257.16.51	81
	dppg.net	124.333.7.87	77
	listserv.org_name.org	124.333.41.40	50
	letters.org_name.org	132.257.16.123	44
	portnoy.org_name.org	132.257.2.11	37
	glacier.org_name.org	132.257.2.152	25
	mailbag.org_name.org	132.257.16.222	22
	sseos.org_name.org	124.333.181.217	21
	ntlin01.dhcp.org_name.org	124.333.183.79	20
	persil.org_name.org	124.333.5.106	20
	beauty8.org_name.org	124.333.5.33	16

A maximum of 20 entries are show.

There are another 39 that are not displayed.

## Top 20 Services

Service	Conn. Count	% of Total	Bytes In	Bytes Out
-----	-----	-----	-----	-----
dns	3378522	75.10	30 G	11 G
http	902573	20.06	18 G	11 G
other	92913	2.07	14 G	249 G
smtp	35942	0.80	458 M	196 M
https	33848	0.75	2.3 G	179 M
ssh	25515	0.57	977 M	1.0 G
netbios-ssn	11004	0.24	65 M	9.5 M
pop-3	5494	0.12	58 M	3.6 M
ftp-data	4495	0.10	37 G	34 G
ldap	3549	0.08	740 K	2.0 M
ftp	1061	0.02	1.3 M	873 K
ident	970	0.02	29602	9039
printer	834	0.02	837	9176
time	645	0.01	2416	166
imap4	636	0.01	28 M	47 M
nntp	308	0.01	355 M	1.5 M
pm_getport	238	0.01	13328	6664
telnet	164	0.00	469 K	7850
ntp	26	0.00	1344	1392
X11	6	0.00	652 K	64280

## Byte Transfer Pairs

**annotation:** *Once again, this summary gives a general idea of what hosts are most active. Radical changes to this list may indicate malicious activity.*

## Hot Report - Top 20

Local Host	Remote Host	Local Bytes	Remote Bytes	Conn. Count
-----	-----	-----	-----	-----
124.333.28.60	128.265.128.131	123 G	5327 K	3930
124.333.28.60	128.265.128.132	123 G	5159 K	3927
132.257.64.3	198.328.2.83	2855 M	11.9 G	15097
124.333.34.186	192.342.93.30	2958 M	10.7 G	40033
132.257.64.3	61.283.32.172	7469 M	10393	11
124.333.41.57	128.256.6.34	12.0 M	4490 M	22360
124.333.181.191	81.257.197.163	1350 M	4430 M	3341
132.257.64.3	130.262.101.6	276 M	2200 M	13064
124.333.34.186	66.263.169.170	389 M	2095 M	17919
132.257.195.68	140.267.28.48	91.3 M	2029 M	6275
132.257.212.232	151.293.199.65	39155	1994 M	24
124.333.41.61	206.290.82.18	3401	1853 M	22
132.257.64.3	61.278.72.30	1798 M	7	1

124.333.181.191	61.263.209.246	16.8 M	1676 M	113
132.257.64.3	261.232.163.3	1544 M	24069	9
132.257.64.3	61.273.210.110	1517 M	4140	7
124.333.34.186	128.342.121.70	1351 M	222 M	14861
132.257.64.3	258.14.200.58	1350 M	24075	14
132.257.64.3	222.330.100.28	1219 M	4077	7
132.257.64.3	210.261.41.131	1162 M	25	3

## 5 Analysis of Incidents and Alarms

### Rule one: There are no rules . . .

This section describes a specific procedure that can be followed with each "incident" that Bro uncovers, but one must keep in mind that intrusion detection is not a static problem. The perpetrators of intrusions and malicious network activity are constantly changing their techniques with the express purpose of evading detection. Unexpected activities are often found by investigation of seemingly innocuous network oddities or serendipitous inspection of logs. While Bro is an exceptionally useful tool for collecting, sorting, analyzing and flagging suspect network data, it cannot be expected to flag all new, cleverly disguised attacks. Nor can it be expected to differentiate with 100% accuracy between aberrant, but legitimate, user behavior and a malicious attack. Sometimes a strong curiosity is an analyst's best friend and Bro is the vehicle for allowing him or her to follow that curiosity.

### 5.1 Two Types of Triggers

There are two ways that alarms can be triggered. One is when network traffic matches a *signatures* that has been converted to work with Bro. The other way is by matching Bro *rules* that are embedded in the Bro analyzers.

#### 5.1.1 Converted Signatures

In the Bro report, converted signatures are identified by the alarm type: **SensitiveSignature** and the existence of a **bro** identification number. Each signature is distinct, targeting one specific set of network events for each alarm. Currently the majority of converted *signatures* are developed from Snort© signatures using the 'snort2bro' utility. In addition, enhancing have been made by utilizing features in the Bro policy language that are absent in Snort©. Most Bro signatures are found in the '\$BROHOME/site/signatures.sig', however, they can exist in other '.sig' files.

#### 5.1.2 Embedded Bro Rule

Bro rules are typically embedded in the Bro *analyzers* or other '.bro' policy files. Several trigger conditions are usually lumped into a grouping of Bro rules within a '.bro' file, making it difficult to separate the exact condition that triggered the alarm. Hence, alarms triggered by an embedded Bro rule will not have a specific **bro** identification number, nor will the *signature code* block appear in the report.

##### Possible types of embedded bro rule alarms:

AddressDropped	AddressScan	BackscatterSeen
ClearToEncrypted_SS	CountSignature	DNS_MappingChanged
DNS_PTR_Scan	FTP_BadPort	FTP_ExcessiveFilename
FTP_PrivPort	FTP_Sensitive	FTP_UnexpectedConn
HTTP_SensitiveURI	HotEmailRecipient	ICMPAsymPayload
ICMPUnpairedEchoReply	ICMPConnectionPair	IdentSensitiveID
LoginForbiddenButConfused	LocalWorm	MultipleSigResponders
MultipleSignatures	OutboundTFTP	PasswordGuessing
PortScan	RemoteWorm	ResolverInconsistency
SSH_Overflow	SSL_SessConIncon	SSL_X509Violation

ScanSummary	SensitiveConnection	SensitiveDNS_Lookup
SensitivePortmapperAccess	SensitiveLogin	SensitiveSignature
SensitiveUsernameInPassword	SignatureSummary	SynFloodEnd
SynFloodStart	SynFloodStatus	TRWAddressScan
TerminatingConnection	W32B_SourceLocal	W32B_SourceRemote
ZoneTransfer		

## 5.2 General Process Steps

The following steps will both aid the Bro user with uncovering network activity of interest, and also help acquaint the user with the anomalies that Bro detects, together building up an understanding of what constitutes "normal" network traffic for the local site. The analyst might follow each successive step with each incident until a firm determination is made if the incident is malicious or a "false positive".

- Understand What Triggered the Alarm(s)
- Understand the Intent of the Alarm(s)
- Examine the Session(s) from the HTTP, FTP, or SMTP Logs
- Examine the Connection Logs for Breakin Indicators
- Examine for Connections to Other Computers
- Examine Other Bro Logs for Odd Activity
- Examine the Bulk Trace if Available
- Contact and Question Appropriate People

## 5.3 Understand What Triggered the Alarm(s)

To understand what triggered the alarm, compare the signature or rule code with *payload*. The network traffic that matches the signature, rule, or policy is known as the payload. The payload that triggers the alarm is usually included in the Bro's incident report. Often it is obvious that the payload is not malicious.

**Example:** The signature may trigger on the word *shadow*, notifying that someone may be attempting to download the shadow password file. However, the payload may reveal that the actual download is something like *theshadow.jpg*, which is obviously innocuous.

The two kinds of alarms, converted signatures and embedded rules trigger alarms differently, so they must be treated separately. The following sections describe how to investigate the signature or rule code and payload of each.

### 5.3.1 Converted Snort Signatures

These signatures are recognizable by the inclusion of a **bro** number and the identification **SensitiveSignature**. A *signature code* and *payload* block should be present in the incident report. To understand what triggered the alarm, compare the payload to the signature code and find the defined signature within the payload. Since some payload lines can get extremely long, the payload lines in the report and notice and alarm logs has been truncated to 250 characters. Sometimes the actual trigger payload is beyond the 250 character cut off. In this case, the protocol sessions log file must be examined. See [Section 5.5 \[Examine HTTP FTP or SMTP Sessions\]](#), page 30.

### 5.3.2 Embedded Bro Rule

For alarms triggered by an embedded Bro rule the *signature code* block will not appear, and in many cases, neither will the payload. There is currently no direct way to find the specific Bro rule that triggered the alarm other than to search the Bro policy files. Following is a process for conducting that search. The example of the HTTP\_SensitiveURL is used. In actual practice, this rule appears quite often in the reports.

**Read about the specific analyzer:** In the Bro Technical Reference Manual there are sections for each type of analyzer. In the case of our example the HTTP analyzer is the obvious choice. In the section on the HTTP analyzer, it is noted that the variables *sensitive\_URIs* and *sensitive\_post\_URIs* are responsible for flagging sensitive URIs.

**Find the policy file that defines these variables:** Using `egrep` to search for *sensitive\_URIs* and/or *sensitive\_post\_URIs* yields the following:

```
> egrep "sensitive_URIs | sensitive_post_URIs" http*
http-request.bro:  const sensitive_URIs =
http-request.bro:  # URIs that match sensitive_URIs but can be generated by worms
http-request.bro:  const skip_remote_sensitive_URIs = /\cgi-bin\/(phf|php\.cgi|
http-request.bro:  const sensitive_post_URIs = /wwwroot|WWWROOT/ &redef;
http-request.bro:  if ( (sensitive_URIs in URI && URI != worm_URIs) ||
http-request.bro:  (method == "POST" && sensitive_post_URIs in URI) )
http-request.bro:  skip_remote_sensitive_URIs in URI )
```

Clearly ‘http-request.bro’ is the file of interest. If, in the case of other types of analyzers, more than one file appears, look for the place where the `const` statement is used to declare the variable(s).

**Look into the policy file:** Search in the section of Bro policy code that describes the rule(s) for the specific notification. In the file ‘http-request.bro’, is found:

```
export{
  const sensitive_URIs =
    /etc.*\/.*(passwd|shadow|netconfig)/
    | /IFS[ \t]*=/
    | /nph-test-cgi\?/
    | /(%0a|\.\.)\.(bin|etc|usr|tmp)/
    | /\Admin_files\order\.log/
    | /\carbo\.dll/
    | /\cgi-bin\/(phf|php\.cgi|test-cgi)/
    | /\cgi-dos\args\.bat/
    | /\cgi-win\uploader\.exe/
    | /\search97\.vts/
    | /tk\.tgz/
    | /ownz/          # somewhat prone to false positives
  &redef;

  # URIs that match sensitive_URIs but can be generated by worms,
  # and hence should not be flagged (because they're so common).
  const worm_URIs =
```



```

        /*.*\c\+dir/
        | /*.*cool.dll.*/*
        | /*.*Admin.dll.*Admin.dll.*/*
    &redef;
}

redef capture_filters += {
    ["http-request"] = "tcp dst port 80 or tcp dst port 8080
                        or tcp dst port 8000"
};

# URIs that should not be considered sensitive if accessed remotely,
# i.e. by a local client.
const skip_remote_sensitive_URIs = /\cgi-bin\/(phf|php\.cgi|test-cgi)/
    &redef;

const sensitive_post_URIs = /wwwroot|WWWROOT/ &redef;

```

Unfortunately, there isn't any way of knowing exactly which one of these rules triggered the `HTTP_SensitiveURL` alarm. As will be seen in the next section, the triggering payload must be compared against this entire section.

## 5.4 Understand the Intent of the Alarm(s)

While understanding the technical signature or policy "code" that "triggered" the alarm, it is also useful to understand the reason the trigger was built.

- What attack or malicious behavior is the alarm trying to illuminate?
- What is the normal method of attack ... manual? automated? expert? novice?
- How long has the particular attack existed?
- How often is it seen? How often is it actually used by attackers?

All of these things, and any other information that can be gathered, will help in differentiating attacks from legitimate behavior. Although this process may seem tedious and time consuming in the beginning, the Bro analyst will quickly build up a substantial knowledge of known attacks. Even if the incident in question turns out to be benign, the effort to learn about the attack almost always proves useful in future investigations.

### 5.4.1 Converted Snort© Signatures

Since Snort© signatures are usually fairly well documented, one way to discover the intent of the signature is to search the web for the title of the signature using any of the common search engines (Yahoo, Google, Teoma, AltaVista, or one of the many others). For instance, a search on the *MS SQL xp\_cmdshell* vulnerability yields ~7000 hits. One of those hits is:

```

Zone-H.org * Advisories
... Successful exploitation of this vulnerability can enable an attacker to
execute commands in the system (via MS SQL xp_cmdshell function). ...
www.zone-h.org/advisories/read/id=4243 - 17k - Cached - Similar pages

```

This web site give a fairly detailed description of the exploit and verifies that it can be used to root compromise a computer and hence, is a vulnerability of significant interest. Several other sites also give details about the signature, the attack, and other useful information.

### 5.4.2 Embedded Bro Rule

Unfortunately, most of the embedded Bro rules have not been documented. The analyst must rely on his/her own understand of network attacks to guess what the intent of the rule is. Sometimes useful comments are written into the Bro policy source.

## 5.5 Examine HTTP FTP or SMTP Sessions

These three files record session activity on ports 80(http), 21(ftp), and 25(smtp) respectively. If the alarm involves any of these ports, these files may reveal the details of the sessions. The general format of all three files is: date/time(SP)%sessionnumber(SP)Message

where:

**date/time:** is the time in UNIX epoch time. The `cf` utility can be used to convert this time to *readable* time. Reference Tech Manual

**sessionnumber:** is the number assigned to session. All subsequent records in the file that are part of the session will retain this same session number. Session numbers are prefixed with the ‘%’ sign.

**message:** is the message that Bro policy has formed to describe the session event. Typically the message will be:

- the start of the session, including the two ip addresses involved
- an anomolous event
- the full protocol command line that was sent
- short statistics concerning the transaction (e.g. bytes sent)

In an alarm where the session number is given (typically in a SensitiveSignature alarm), a search on the session number in the appropriate file(s) will show the full sessions. See [Section A.7 \[The bro/logs Directory\]](#), page 54.

#### Example:

Consider the following alarm:

```
Alarm: HTTP_SensitiveURI
      11/22_12.52.42                128.333.48.179 -> 80.143.378.186
                                   3091/tcp -> 80/tcp

      session: %73280
      payload: GET\NR\rdonlyres/eirownz4tqwlseoggqm2ahj5cqsdbedlaxyye
              7kvdz7rnh6u4o2v2gpvmoggqjlekzdtulryyatiinj3xwimmiavgfb/
              smallshoulders.gif\ (200\ "OK"\ [1134])
```

From the payload shown, it is unclear what triggered the alarm. To investigate further, the entire session can be viewed:

Example:

```
> grep %73280 http.hostname.04-11-22_12.52.42 | cf
Nov 22 15:18:30 %73280 start 128.333.48.179 > 80.143.378.186
Nov 22 15:18:30 %73280 GET /fitness/default.htm (200 "OK" [10473])
Nov 22 15:18:30 %73280 GET /javascripts/cms_common.js (304 "Not Modified"[0])
Nov 22 15:19:47 %73280 GET /food_nutrition/default.htm (200 "OK"[13177])
Nov 22 15:19:47 %73280 GET /NR/rdonlyres/eirwwu3xtlr22dkat5cim4ziupouzxb6kz4xb
zbr4zs255ca57cvv5mhcjcrmrfg6kpcrevyndo2za3yoi5esheiolf/News111904Dairy NotFor
Diet.jpg (200 "OK" [6572])
Nov 22 15:19:51 %73280 GET /NR/rdonlyres/0D25692F-D59A-4B90-AB53-8BBC9E75A286.
gif (200 "OK" [189])
Nov 22 15:19:51 %73280 GET /NR/rdonlyres/eqpbdex34wpqpap2fcbxh35omcjtq45feyf7
zgtjff6fhrybfbvtszeu4rc2clayghhslfimaafkoocae6cv6wof/doctor.jpg (200 "OK" [161
5])/NR/rdonlyres/enhskrfoodzuquvmbli2hasjspusrgsvyhd3nlue5msoli2ueagrwdxw56gga
aa7sosee3yn2hwywgc6kgv4wcv6jc/bigback.gif (200 "OK" [8192 (interrupted)])/NR/rd
onlyres/ej2cpd275ghrefp23ezou43haqe6fmj3oyeqxkvopf4bv4zhwbqimfrrbndqpotx55pogc7
xiqvdcovaxo66afyqfof/smallleg.jpg (200 "OK" [1010])
Nov 22 15:22:12 %73280 GET /NR/rdonlyres/eirownz4tqwlseoggqm2ahj5cqsdbedlaxyye7
kvdz7rn6u4o2v2gpvmoggqjlekdztulryyatiinj3xwimmiavgfb/smallshoulders.gif (200 "
OK" [1134])
Nov 22 15:22:13 %73280 GET /NR/rdonlyres/49D86A33-AF6C-4873-AD11-F26DDBF222B1.g
if (200 "OK" [167])
```

By examining this session it can clearly be seen that the session is simply a web visit to a fitness website. There is no need to investigate further.

## 5.6 Examine the Connection and Weird Logs

The connection logs are a record of every connection Bro detects. Although they don't contain content, being able to track the network *movement* of an attacking host is often very useful.

### 5.6.1 Breakin Indicators

If it is still not clear if a suspect host is an attacker, the connection surrounding the suspicious connection can be examined. Here are some questions that might be answered by the 'conn' logs.

- itemize item How many more successful connection the attacker make to the target host?
- item How much data was transferred? A lot of data means something more than an unsuccessful probe.
- item Did the target host connect back to the attacker? This is a fairly sure sign of a successful attack. The attacker has gained control of the target and is connecting back to his own host.
- item What was the time duration? If several attacks occur in a very short time and then slow down to *human* speed, it could indicate the attacker used an automated attack to gain control and then switched to a manual mode to "work on" the compromised target host.

### 5.6.2 Connections to Other Computers

If a host has been successfully identified as an attacker, it is useful to know what and how many other hosts the attacker has touched. This can be found by grepping through the 'conn' logs for instances of connections by the suspect host.

example here

If the attack used a specific, little used, port; another investigation would be to search for other similar connection using that port. Often the attacker might change attack hosts, but will continue to use the same attack method.

**example here**

**NOTES:** *You may want to go back several days, weeks, months, or even years to see if the attacker has visited (and perhaps compromised) your site earlier without being detected.*

*However, be forewarned that the ‘conn’ logs tend to get very large and doing extensive searches can take a very long time.*

### 5.6.3 Odd Activity

Despite attempts to have the network community adhere to network standards, non-compliant traffic occurs all the time. The ‘weird’ logs are a record of instances of network traffic that simply should not happen.

While these logs are usually of interest to the most hard-core of network engineers, if a unique attack is detected, it is sometimes valuable to search the weird logs for other unusual activities by the attacking host. Hackers are not bound by standard protocol and sometimes find ways to circumvent security via *weird* methods.

## 5.7 Examine the Bulk Trace if Available

For information on using the Bulk trace files for analysis, see [Chapter 9 \[Bulk Traces and Off-line Analysis\]](#), page 45.

## 5.8 Contact and Question Appropriate People

The final and usually the most definitive investigation is to call the owners of the hosts involved. Often a call to the owner of the local host can reveal that the activity was not normal, but appropriate or a mistake.

## 6 Customizing Bro

Bro is very customizable, and there are several ways to modify Bro to suit your environment. You can write your own policy analyzers using the Bro language. Most sites will likely just want to do minor customizations, such as changing the level of an alert from "notice" to "alarm", or turning on or off particular analyzers. The chapter describes how to do these types of customizations. Information on how to write your own analyzers can be found in the [Bro Reference Manual](#).

The default policy scripts for Bro are all in \$BROHOME/policy. These files should **never** be edited, as your edits will be lost when you upgrade Bro. To customize Bro for your site, you should make all your changes in \$BROHOME/site. Many simple changes just require you to *redefine* (using the **redef** operator, a Bro constant from a standard policy script with your own custom value. You can also write your own custom script to do whatever you want.

For example, to add "guest" to the list of **forbidden\_ids** (user names that generate a login alarm), you do this:

```
redef forbidden_ids += { "guest", };
```

In this chapter we give an overview of all the standard Bro policy scripts, what notices they generate, and how to customize the most commonly changed items.

### 6.1 Policy Files

Bro *policy* script is the basic analyzer used by Bro to determine what network events are alarm worthy. A policy can also specify what actions to take and how to report activities, as well as determine what activities to scrutinize. Bro uses policies to determine what activities to classify as *hot*, or questionable in intent. These hot network sessions can then be flagged, watched, or responded to via other policies or applications determined to be necessary, such as calling **rst** to reset a connection on the local side, or to add an IP address block to a main router's ACL (Access Control List). The policy files use the Bro scripting language, which is discussed in great detail in [The Bro Reference Manual](#).

Policy files are loaded using an **@load** command. The semantics of **@load** are "load in this script if it hasn't already been loaded", so there is no harm in loading something in multiple policy scripts. The following policy scripts are included with Bro. The first set are all on by default, and the second group can be added by adding them to your 'site/local.site.bro' policy file.

Bro Analyzers are described in detail in the [Reference Manual](#). These policy files are loaded by default:

<b>site</b>	defines local and neighbor networks from static config
<b>alarm</b>	open logging file for alarm events
<b>tcp</b>	initialize BPF filter for SYN/FIN/RST TCP packets
<b>login</b>	rlogin/telnet analyzer (or to ensure they are disabled)
<b>weird</b>	initialize generic mechanism for detecting unusual events
<b>conn</b>	access and record connection events
<b>hot</b>	defines certain forms of sensitive access
<b>frag</b>	process TCP fragments
<b>print-resources</b>	on exit, print resource usage information, useful for tuning

<code>signatures</code>	the signature policy engine
<code>scan</code>	generic scan detection mechanism
<code>trw</code>	additional, more sensitive scan detection
<code>http</code>	general http analyzer, low level of detail
<code>http-request</code>	detailed analysis of http requests
<code>http-reply</code>	detailed analysis of http replies
<code>ftp</code>	FTP analysis
<code>portmapper</code>	record and analyze RPC portmapper requests
<code>smtp</code>	record and analyze email traffic
<code>tftp</code>	identify and log TFTP sessions
<code>worm</code>	flag HTTP-based worm sources such as Code Red
<code>software</code>	track software versions; required for some signature matching
<code>blaster</code>	looks for blaster worm
<code>synflood</code>	looks for synflood attacks
<code>stepping</code>	used to detect when someone logs into your site from an external net, and then soon logs into another site
<code>reduce-memory</code>	sets shorter timeouts for saving state, thus saving memory. If your Bro is using < 50% of you RAM, try not loading this

These are **not** loaded by default:

<b>Policy</b>	<b>Description</b>	<b>Why off by default</b>
<code>drop</code>	Include if site has ability to drop hostile remotes	Turn on if needed
<code>icmp</code>	icmp analysis	CPU intensive and low payoff
<code>dns</code>	DNS analysis	CPU intensive and low payoff
<code>ident</code>	ident program analyzer	historical, no longer interesting
<code>gnutella</code>	looks for hosts running Gnutella	Turn this on if you want to know about this
<code>ssl</code>	ssl analyzer	still experimental
<code>ssh-stepping</code>	Detects stepping stones where both incoming and outgoing connections are ssh	Possibly too CPU intensive (needs more testing)
<code>analy</code>	Performs statistical analysis	only used in off-line analysis
<code>backdoor</code>	Looks for backdoors	only effective when also capturing bulk traffic
<code>passwords</code>	Looks for clear text passwords	may want to turn on if your site does not allow clear text passwords
<code>file-flush</code>	Causes all log files to be flushed every N seconds	may want to turn on if you are doing "real time" analysis

To modify which analyzers are loaded, edit or create a file in `'BROHOME/site'`. If you write your own new custom analyzer, it goes in this directory too. To disable an analyzer, add `"@unload policy.bro"` to the beginning of the file `'BROHOME/brohost.bro'`, before the line `"@load brolite.bro"`. To add additional analyzers, add them `@load` them in `'BROHOME/site/local.site.bro'`.

## 6.2 Notices

The primary output facility in Bro is called a *Notice*. The Bro distribution includes a number of standard of Notices, listed below. The table contains the name of the Notice, what Bro policy file generates it, and a short description of what the Notice is about.

Notice	Policy	Description
AckAboveHole	weird	Could mean packet drop; could also be a faulty TCP implementation
AddressDropIgnored	scan	A request to drop connectivity has been ignored ; (scan detected, but one of these flags is true: !can_drop_connectivity, or never_shut_down, or never_drop_nets )
AddressDropped	scan	Connectivity w/ given address has been dropped
AddressScan	scan	The source has scanned a number of addrs
BackscatterSeen	scan	Apparent flooding backscatter seen from source
ClearToEncrypted_SS	stepping	A stepping stone was seen in which the first part of the chain is a clear-text connection but the second part is encrypted. This often means that a password or passphrase has been exposed in the clear, and may also mean that the user has an incomplete notion that their connection is protected from eavesdropping.
ContentGap	weird	Data has sequence hole; perhaps due to filtering
CountSignature	signatures	Signature has triggered multiple times for a destination
DNS_MappingChanged	DNS	Some sort of change WRT previous Bro lookup
DNS_PTR_Scan	dns	Summary of a set of PTR lookups (automatically generated once/day when dns policy is loaded)
DroppedPackets	netstats	Number of packets dropped as reported by the packet filter
FTP_BadPort	ftp	Bad format in PORT/PASV;
FTP_ExcessiveFilename	ftp	Very long filename seen
FTP_PrivPort	ftp	Privileged port used in PORT/PASV
FTP_Sensitive	ftp	Sensitive connection (as defined in <i>hot</i> )
FTP_UnexpectedConn	ftp	FTP data transfer from unexpected src
HTTP_SensitiveURI	http	Sensitive URI in GET/POST/HEAD (default sensitive URIs defined http-request.bro; e.g.: /etc.*\/*.*(passwd shadow netconfig)
HotEmailRecipient	smtp	XXX Need Example, default = NULL
ICMPAsymPayload	icmp	Payload in echo req-resp not the same



ICMPConnectionPair	icmp	Too many ICMPs between hosts (default = 200)
IdentSensitiveID	ident	Sensitive username in Ident lookup
LocalWorm	worm	Worm seen in local host (searches for code red 1, code red 2, nimda, slammer)
LoginForbidden	login	Interactive login seen using forbidden username, but the analyzer was confused in following the login dialog, so may be in error.
ButConfused		host has triggered the same signature on multiple responders
Multiple	signatures	host has triggered many signatures
SigResponders	signatures	host has triggered the same signature on multiple responders
MultipleSignatures	signatures	multiple responders
Multiple	signatures	outbound TFTP seen
SigResponders	tftp	source tried too many user/password combinations (default = 25)
OutboundTFTP	scan	the source has scanned a number of ports
PasswordGuessing	scan	worm seen in remote host
PortScan	scan	the answer returned by a DNS server differs from one previously returned
RemoteWorm	worm	prints Bro resource usage
Resolver	dns	possible evasion; usually just bad TCP implementation
Inconsistency	print-resources	session data not consistent with connection
ResourceSummary	weird	blanket X509 error
Retransmission	weird	a summary of scanning activity, output once / day
Inconsistency	weird	connection marked "hot", See: <a href="#">Reference Manual section on hot ids</a> for more information.
SSL_SessConIncon	ssl	DNS lookup of sensitive hostname/addr; default list of sensitive hosts = NULL
SSL_X509Violation	ssl	interactive login using sensitive username (defined in 'hot')
ScanSummary	scan	the given combination of the service looked up via the portmapper, the host requesting the lookup, and the host from which it's requesting it is deemed sensitive
SensitiveConnection	conn	generic for alarm-worthy
SensitiveDNS_Lookup	dns	During a login dialog, a sensitive username (e.g., "rewt") was seen in the user's password. This is reported as a notice because it could be that the login analyzer didn't track the authentication dialog correctly, and in fact what it thinks is the user's password is instead the user's username.
SensitiveLogin	login	summarize number of times a host triggered a signature (default = 1/day)
SensitivePortmapperAccess	portmapper	
SensitiveSignature	signatures	
SensitiveUsername	login	
InPassword		
SignatureSummary	signatures	



SynFloodEnd	synflood	end of syn-flood against a certain victim. A syn-flood is defined to be more than SYN-FLOOD_THRESHOLD (default = 15000) new connections have been reported within the last SYNFLOOD_INTERVAL (default = 60 seconds) for a certain IP.
SynFloodStart	synflood	start of syn-flood against a certain victim
SynFloodStatus	synflood	report of ongoing syn-flood
TRWAddressScan	trw	source flagged as scanner by TRW algorithm
TRWScanSummary	trw	summary of scanning activities reported by TRW
Terminating Connection	conn	"rst" command sent to connection origin, connection terminated, triggered in the following policies: ftp and login: forbidden user id, hot (connection from host with spoofed IP address)
W32B_SourceLocal	blaster	report a local W32.Blaster-infected host
W32B_SourceRemote	blaster	report a remote W32.Blaster-infected host
WeirdActivity	Weird	generic unusual, alarm-worthy activity

To get a list of all Notices that your particular Bro configuration might generate, you can type:

```
sh . $BROHOME/etc/bro.cfg; bro -z notice $BRO_HOSTNAME.bro
```

## 6.3 Notice Actions

Notices that are deemed particularly important are called *Alarms*. Alarms are sent to the alarm log file, and to optionally to *syslog*.

The standard Bro distribution supports a number of types of *notice actions*, these are:

NOTICE_IGNORE	do nothing
NOTICE_FILE	send to 'notice' file
NOTICE_ALARM_ALWAYS	send to alarm file and <i>syslog</i>
NOTICE_ALARM_PER_CONN	send to alarm file once per connection
NOTICE_ALARM_PER_ORIG	XXX not used, so remove?
NOTICE_ALARM_ONCE	XXX not used, so remove?
NOTICE_ALARM_EMAIL	send to alarm file and send email

It is also possible to define your own custom notice actions.

By default, all notices are set to NOTICE\_ALARM\_ALWAYS except for the following:

ContentGap, AckAboveHole, AddressDropIgnored, PacketsDropped,  
RetransmissionInconsistency

To also send all Alarms to *syslog*, set this in 'BROHOME/local.site.bro':

```
redef syslog_alarms = T;
```

To change the default notice action for a given notice, add something like this to your 'site/local.site.bro' file:

```
redef notice_action_filters += {  
    [[WeirdActivity, ContentGap]] = ignore_notice,
```

```
};
```

This will cause the Notices `WeirdActivity` and `ContentGap` to no longer get logged anywhere. To send these Notices to the Notice log file only, and not to the Alarm log, add this:

```
redef notice_action_filters += {
    [[WeirdActivity, ContentGap]] = file_notice,
};
```

## 6.4 Signatures

NOTE: this section rough and somewhat in flux

Signatures in Bro are quite different than standard packet matching signatures such as those used in [Snort](#). A Bro signature, or *Rule*, is a *contextual signature* that can include connection-level information. Hence Bro signatures generate **far** fewer false positives.

For example, an packet-level signature of a HTTP attack only looks at the attack packet, where the Bro contextual signature also looks for the HTTP reply, and only generates an alarm if the attack was successful.

In this section we explain how to customize signatures for your site, and how to import new signatures from Snort and bro-ids.org. More information on the details of Bro signatures are in [the signature section of the reference manual](#).

The following files are used to control and customize Bro signatures.

- `$BROHOME/site/signatures.sig`: Bro version of snort signatures
- `$BROHOME/policy/sig-addendum.sig`: Bro supplied signatures
- `$BROHOME/policy/sig-action.bro`: policy file to control signature notification type

Files in `$BROHOME/policy` contain the default Bro signatures, and should not be edited. Files in `$BROHOME/site` contain files you will use to customize signatures for your site. New signatures that you write go here too. All files ending in `.sig` in this directory will be loaded into the signature engine. In fact, all `.sig` files in any directory in `$BROPATH` (set in `$BROHOME/etc/bro.cfg`) will be loaded.

### 6.4.1 Turning Signatures ON/OFF

Signature "action" levels are controlled by the file `$BROHOME/site/sigaction.bro`. You can set the signature action to the one of the following:

```
SIG_IGNORE      # ignore this sig. completely
SIG_FILE        # write to signatures and notice files
SIG_ALARM       # alarm and write to notice and alarm files
SIG_ALARM_PER_ORIG # alarm once per originator
SIG_ALARM_ONCE  # alarm once and then never again
```

All signatures default to action = `SIG_ALARM`. To lower the alarm level of the signature, add an entry to the file `$BROHOME/site/sigaction.bro`. The Bro distribution contains a default `sigaction.bro` file that lowers the level of a number of signatures from `ALARM` to `FILE` (notice) .

To permanently remove a signature you can delete it from the `.sig` file.

### 6.4.2 Add a New Signature

To add a new signature to a running Bro, add the signature to the file `site/site.sigs` (or create a new `.sig` file in that directory), and then restart Bro using `"$BROHOME/etc/bro.rc checkpoint"`.

A sample signature looks like this:

```
signature formmail-cve-1999-0172 {
    ip-proto == tcp
    dst-ip == 1.2.0.0/16
    dst-port = 80
    http /. *formmail.*\?.*recipient=[^&]*[;|]/
    event "formmail shell command"
}
```

For more details, see the [reference manual](#).

### 6.4.3 Editing Existing Signatures

Bro supplied signatures are in `$BROHOME/sigs`. You should not edit these, as they will get overwritten when you update Bro. Instead, make your modifications in `$BROHOME/site`. If you use the same signature ID as an existing signature, the site sig will take precedence.

### 6.4.4 Importing Snort Signatures

New snort signatures come out almost every week. To add these to Bro, do the following:

(XXX section not done!)

Add instructions for incorporating new sigs from Snort.

### 6.4.5 Checking for new Signatures from [bro-ids.org](#)

note: this functionality is currently under development, and does not yet exist

The Bro team will be constantly updating our set of default signatures and posting them on the Bro web site. To download the latest signatures and incorporate them into your Bro setup, run the script:

```
$BROHOME/scripts/update-sigs
```

This script uses the `wget` command to download the latest signatures and puts them into the required Bro files, and then restarts Bro to load the new signatures..

## 6.5 Tuning Scan Detection

There are a large number of tunable parameters in the scan analyzer, all of which are described in [the reference manual](#). Most of these parameters should be fine for all sites. The only settings that you may want to tune are:

- `report_peer_scan`: Generate a log message whenever a remote host has attempted to connect to the given number of distinct hosts. Default = { 100, 1000, 10000, }.
- `report_outbound_peer_scan`: Generate a log message whenever a local host has attempted to connect to the given number of remost hosts. Default = { 100, 1000, }.

- `skip_services`: list of ports to ignore scans on, because they often gets scanned by legitimate (or at least common) services. The default list can be found in the `brolite.bro` file.

If you want enable ICMP scan detection, set these:

```
redef ICMP::detect_scans = T;
redef ICMP::scan_threshold = 100;
```

## 6.6 Other Customizations

There are a number of things you may wish to customize.

### hot\_ids

The policy file `'hot-ids.bro'` contains a number of constants that you might want to customize by "redef"ing them in your `local.site.bro` policy file. These are all used to generate FTP and login alarms (SensitiveConnection Notice) for suspicious users. The user ID's that are in `hot_ids` and not in `always_hot_ids` are only hot upon successful login. For details see the [Bro Reference Manual](#).

constant	Defaults
<code>forbidden_ids</code>	"uucp", "daemon", "rewt", "nuucp", "EZsetup", "OutOfBox", "4Dgifts", "ezsetup", "outofbox", "4dgifts", "sgiweb", "r00t", "ruut", "bomb", "back-door", "bionic", "warhead", "check_mate", "check-mate", "check_made", "themage", "darkmage", "y0uar3ownd", "netfrack", "netphrack"
<code>always_hot_ids</code>	"lp", "demos", "retro", "milk", "moof", "own", "gdm", "anacnd", + <code>forbidden_ids</code>
<code>hot_ids</code>	"root", "system", "smtp", "sysadm", "diag", "sys-diag", "sundiag", "sync", "tutor", "tour", "operator", "sys", "toor", "issadmin", "msql", "sysop", "sysoper", + <code>always_hot_ids</code>

### Input/Output Strings

The policy files `login.bro` and `ftp.bro` both contain a list of input and output strings that indicate suspicious activity. In you wish to add anything to this list, you may want to **redef** one of these.

`login.bro`: see [input\\_trouble](#) and [output\\_trouble](#)

`ftp.bro`: see [ftp\\_hot\\_files](#)

### Sensitive URIs

The policy file `http-request.bro` contain a list of http URI's that indicate suspicious activity. In you wish to add anything to this list, you may want to **redef** one of these.

`sensitive_URIs`

`sensitive_post_URIs`

### Log Files

**redef** this to rotate the log files every N seconds

`log_rotate_interval` (default = 0 sec, don't rotate)

**redef** this to rotate the log files when they get this big

```
log_max_size (default = 250e6, rotate when any file exceeds 250 MB)
```

## 7 Intrusion Prevention Using Bro

Bro includes two important *active response* capabilities that allow sites to use Bro for intrusion prevention, and not just intrusion detection. These include the ability to terminate a connection known to be an intrusion, and the ability to update a blocking router's access control list (ACL) to block attacking hosts.

### 7.1 Terminating a connection

The Bro distribution includes a program called `rst` that will terminate a active connection by sending a TCP "reset" packet to the sender. The `ftp` and `login` analyzers look for connections that should be terminated. All connections from a `forbidden_id` get flagged for termination, as well as any service defined in `terminate_successful_inbound_service`.

Connection termination is off by default. To enable it, redefine the following flag in your `'site/site.local.bro'` file:

```
redef activate_terminate_connection = T ;
```

Whenever a connection is terminated you will see a `TerminatingConnection` alarm. If Bro detects a connection that Bro thinks is a candidate for termination, but `activate_terminate_connection = F`, then you will see the alarm: `IgnoreTerminatingConnection`.

You may want to add a number of services to the list of forbidden services. For example, to terminate all successful attempts to access the RPC portmapper via TCP from an external network, you would add this:

```
redef terminate_successful_inbound_service += {
    [111/tcp] = "disallow external portmapper"
};
```

This will prevent NFS connections from external hosts. P2P services such as KaZaa can also be terminated in this manner. You can make exceptions to `terminate_successful_inbound_service` by redefining `allow_services_to`. See `hot.bro` for details.

*Note: should include a more complex example here.*

### 7.2 Updating Router ACL

Bro can be used to send the IPs of scanning or attacking hosts to your router, so that the router can drop these hosts.

Since every router does this differently, you will need to write a script that works for your router. The Bro distribution contains a simple sample script which is installed as `'$BROHOME/scripts/sample_router_update.sh'` (coming soon).

To active your custom drop script, add this to you `site.local.bro` file:

```
@load drop
redef can_drop_connectivity = T;
redef drop_connectivity_script = "my_drop_script";
more details coming soon
```

## 8 Performance Tuning

**NOTE: This chapter still a rough draft and incomplete**

If the link you are monitoring with Bro has too many connections per second, or if you have too many policy modules loaded, it is possible that Bro will not be able to keep up, and that the Bro host will drop too many packets to be able to perform accurate analysis.

A "rule of thumb" for Bro is that if CPU usage is < 50% and memory use is < 70% of physical memory, than you should not have any worries.

Otherwise you might want to explore the tuning options below.

For sites with an extremely high load you might consider using multiple Bro boxes, each configured to capture and analyze different types of traffic.

Note that the amount of CPU required by Bro is a function of both the number of connections/second and the number of packets/second. So it's possible that a large site (e.g., 2,000 hosts) on a slow link (e.g., 100 Mbps) would still have performance issues because it has a very large number of connections / second.

### 8.1 Hardware and OS Tuning

If your CPU load > 50% or your memory footprint is > 70% of physical memory, an obvious solution is to buy a faster CPU or more memory.

If this is not possible, here are some other things to try.

#### FreeBSD

First, check that your BPF buffer size is big enough. The Bro installation script should set this correctly for you, but to test this, do:

```
sysctl debug.bpf_bufsize
sysctl debug.bpf_maxbufsize
```

They should both be at least 4 MB.

Next, if your Bro host is capturing packets on 2 interfaces and you are running FreeBSD, we provide a patched kernel that bonds both interfaces into a single interface at the BPF level. This reduces CPU load considerably. This patched kernel also increases the default per-process memory limits.

This kernel source is available for download at:

<http://www.bro-ids.org/download/FreeBSD.4.10.bro.tgz>.

To install this kernel and the BPF bonding utilites, type:

```
tar xzf fbsd.4.10.bond.tgz
cd FreeBSD-4-10-RELEASE/sys/i386/conf
/usr/sbin/config BRO
cd ../../compile/BRO
make depend
make
make install

cd FreeBSD-4-10-RELEASE/local/sbin/bpfbond/
make
make install

reboot
```

For more instructions on rebuilding the kernel, see: [http://www.freebsd.org/doc/en\\_US.ISO8859-1/books/handbook/kernelconfig.html](http://www.freebsd.org/doc/en_US.ISO8859-1/books/handbook/kernelconfig.html).

### Linux

XXX section not done.

There are a number of patches needed to make Bro work well with Linux on sites with a heavy traffic load.

These include:

Luca Deri's patch to fix libpcap issues. (see: <http://luca.ntop.org/Ring.pdf>)

## 8.2 Bro Policy Tuning

If the hardware and OS tuning solutions fail to bring your CPU load or memory consumption under control, next you will have to start turning off analyzers. Signatures are particularly CPU and memory intensive, so try turning it off or greatly reduce the number of signatures it is processing. The HTTP analyzers are also CPU intensive. For example, to turn off the HTTP reply analyzer, add the following lines to `$BROHOME/site/local.site.bro`

```
@unload http-reply
```

Another solution is to modify libpcap filter for Bro. This is done by adding `restrict_filters`. For example, to only capture SYN/FIN packets from a large web proxy, you can do this:

```
redef restrict_filters += { ["not proxy outbound Web replies"] =
    "not (host bigproxy.mysite.net and
        src port 80 and (tcp[13] & 7 == 0))" };
```

This filter will allow you to record the number and size of the HTTP replies, but will not do further HTTP analysis.

XXX: explain how to turn off signatures

XXX: explain how to split traffic across 2 bro boxes



## 9 Bulk Traces and Off-line Analysis

**NOTE: This chapter still a very rough draft and incomplete**

Bro is most effective when used in conjunction with bulk traces from your site. Capturing bulk traces just involves using `tcpdump` to capture all traffic entering and leaving your site.

Bulk traces can be very valuable for forensic analysis of all traffic in and out of a compromised host. It is also needed to run some particularly CPU intensive policy analyzers that can not be done in real time (as described in the Off-line Analysis section below).

Depending on your traffic load, you might be able to bulk capture on the Bro host directly, but in general we recommend using a separate packet capture host for this. Unless you want to buy a huge amount of disk, you'll probably only be able to save a few days worth of traffic.

### 9.1 Bulk Traces

The Bro distribution includes a couple scripts to make bulk capture easier. These are:

**spot-trace:** called by **start-capture-all** script

**start-capture-all:** captures all packets. This script looks for an existing instance of the **spot-trace** program, and if it finds one creates a new capture file name with an incremented filename, and continues capturing data. Bulk capture files can get very large, so typically you run this as a cron job every 1-2 hours.

**bro\_bulk\_compress.sh:** compress and/or delete old bulk trace files. Run as a cron job.

Since the bulk trace files can be huge, you often will want to run `tcpdump` on the raw trace with a filter to extract the packets of interest. For example:

```
tcpdump -r bulkXXX.trace -w goodstuff.trace 'host w.x.y.z'
```

If you know that that packets you want are bounded by a time interval, say it occurred 1:17PM-1:18PM, then you can speed this up a great deal using **tcpslice**. For example:

```
tcpslice 13h15m +5m bulkXXX.trace | tcpdump -r - -w goodstuff.trace 'host w.x.y.z'
```

It is recommend to use a somewhat broader time interval for `tcpslice` (such as in the above example) than when Bro reported the activity occurred, so you can catch additional related packets cheaply.

### 9.2 Off-line Analysis

There are some policy modules that are meant to be run as off-line analysis on bulk trace files. These include:

**backdoor.bro:** looks for standard services running on non-standard ports. These services include ssh, http, ftp, telnet, and rlogin.

To run Bro on a `tcpdump` file, do something like this:

```
# set up the Bro environment (sh or bash)
. /usr/local/bro/etc/bro.cfg
/usr/local/bro/bin/bro -r dumpfile backdoor.bro
```

To use Bro to extract the contents of a trace file, do:

```
bro -r tracefile contents
```

which will load `policy/contents.bro`. It stores the contents of each connection in two files, `contents.H1.P1.H2.P2` and `contents.H2.P2.H1.P1`, where H1/P1 is the host/port of the originator and H2/P2 the same for the responder.

You can extract just the connections of interest using, for example:

```
bro -f "host 1.2.3.4" -r tracefile contents
```

## Appendix A Bro Directory and Files




Figure A.1: The Bro Directory Structure

### A.1 The bro/bin Directory

The bin directory is the storage area for executable binary files used by Bro.

#### **adtrace**

adtrace retrieves MAC and IP address information from tcpdump trace files

usage:

```
adtrace <trace-file>
```

#### **bro**

This program is the primary Bro executable. Full use of the bro command is documented in the technical manual.

**cf**

A program that converts UNIX epoch time into a conventional date. Most of the raw Bro logs record UNIX epoch time as the timestamp for their records. Piping the file through cf will convert the time. Full use of cf is documented in the technical manual.

**rst**

A program that Bro calls to form and send a reset packet which will tear down a tcp connection. The use of rst is documented in the Technical Manual and in chapter ### of the User Manual.

## A.2 The bro/etc Directory

Configuration and other ancillary files are stored in the etc directory. These files are usually changed by supplementary configuration tools supplied with the Bro distribution. Direct editing of these files is discouraged. If direct edits are made, the changes may be reversed or deleted during subsequent Bro updates.

**alert\_scores**

This file contains ranking numbers for alarms (the use of the term "alert" is vestigial and will be changed in the future). The ranking numbers are used as part of the ranking system for determining the success likelihood of an incident triggering a specific alarm.

**bro.cfg**

This file contains configuration criteria for operational parameters. Most of the parameters are set during the installation process and can be changed using the bro- config script.

**bro.cfg.example**

A annotated, generic bro.cfg file. This file is not used by Bro. It is supplied for documentation purposes.

**bro.rc**

This is the script for controlled starting and stopping of Bro. See section ### for its use.

**bro.rc-hooks.sh**

This script is called by bro.rc at various points during the starting and stopping of Bro. It is presented as an interface for customizations into the start and stop process.

**signature\_scores**

This file contains ranking numbers for signatures. The ranking numbers are used as part of the ranking system for determining the success likelihood of an incident triggering a specific signature.

**VERSION**

A file containing the Bro version number for the installed distribution.

### A.3 The bro/var Directory

Temporary information about the current Bro instance is stored in the var directory.

#### **autorestart**

Contains the word "ON" if Bro is configured to autorestart.

#### **pid**

Contains the process ID number for the current instance of Bro.

#### **start\_time**

Contains the date and time when the current instance of Bro was started.

### A.4 The bro/scripts Directory

This directory contains a number of auxiliary scripts used to suppliment Bro's operation.

#### **bro-config**

A utility script for changing the Bro operational parameters in the bro.cfg file.

#### **bro-logchk.pl**

*Currently, this file does not work*

A utility program for searching ftp and http log files for activity by specific ip addresses.

Usage:

```
bro-logchk.pl -[hrDFHds] -f filename -a ipaddr -x ipaddr
-h          print this usage information
-F          using ftp log
-H          using http log
-r          try to resolve IP addresses to hostnames
-f file     log file to parse
-a ipaddr   only output connections from this address
-s          only want matching source address (used with -a )
-d          only want matching dest address (used with -a )
-D          debug option
-x ipaddr   exclude connections from this address
```

#### **bro\_log\_compress.sh**

A very simple script written to manage log and coredump files. By default it compresses log files older than 30 days and sends them to the archive directory; it deletes log files older than 60 days; and it deletes coredump files older than 4 days.

Restrictions:

- Must be run from a user account that has read/write/execute access to files in the \$BROHOME directory.

## host-grep

Grep a Bro connection summary log on stdin for two given hostnames.

Usage:

```
host-grep [-a] hostname hostname < connection_log
If -a is specified then we only want lines with *all* of the listed hosts.
```

Restrictions:

- Must have \$BROHOME/scripts included in the PATH environment variable.
- Will only work with hostnames. ip addresses are not accepted
- Uses host-to-addr and ip-grep scripts

## host-to-addr

Finds all ip addresses associated with a given hostname.

Usage:

```
host-to-addr hostname
```

Restrictions:

- Must have \$BROHOME/scripts included in the PATH environment variable.
- Will only work with hostnames. IP addresses are not accepted

## ip-grep

Returns an exact grep pattern for matching the IP addresses of the given hosts

Usage:

```
ip-grep hostname hostname ...
```

Restrictions:

- Must have \$BROHOME/scripts included in the PATH environment variable.
- Will only work with hostnames. ip addresses are not accepted
- Uses host-to-addr script

## site-report.pl

This script produces the daily consolidated site report. By default, it is run daily via the cron job submitted by the bro user via files in /var/cron/tabs.

## The bro/scripts/pm Directory

This directory contains perl modules to support the perl scripts in the scripts directory.

## A.5 The bro/policy Directory

This directory contains all standard Bro policy files. For more information about the policy files see section ###, Policy

Signature support files:

**sig-addendum.sig**

This file contains small support utilities that are used in the implementation of Bro signatures.

**sig-functions.bro**

*To be completed*

**sig-action.bro**

*To be completed*

Policy files:

- active.bro
- alarm.bro
- analy.bro
- anon.bro
- backdoor.bro
- blaster.bro
- bro.bif.bro
- bro.init
- brolite.bro
- capture-events.bro
- checkpoint.bro
- common-rw.bif.bro
- conn-id.bro
- conn.bro
- const.bif.bro
- contents.bro
- cpu-adapt.bro
- demux.bro
- dns-info.bro
- dns-lookup.bro
- dns.bro
- drop-adapt.bro
- event.bif.bro
- finger-rw.bif.bro
- finger.bro
- flag-irc.bro
- flag-warez.bro
- frag.bro
- ftp-anonymizer.bro

- ftp-cmd-arg.bro
- ftp-reply-pattern.bro
- ftp-rw.bif.bro
- ftp-safe-words.bro
- ftp.bro
- gnutella.bro
- hand-over.bro
- hot-ids.bro
- hot.bro
- http-abstract.bro
- http-body.bro
- http-entity.bro
- http-event.bro
- http-header.bro
- http-reply.bro
- http-request.bro
- http-rewriter.bro
- http-rw.bif.bro
- http.bro
- icmp.bro
- ident-rewriter.bro
- ident-rw.bif.bro
- ident.bro
- inactivity.bro
- interconn.bro
- listen-clear.bro
- listen-ssl.bro
- load-level.bro
- login.bro
- mime.bro
- mt.bro
- netstats.bro
- notice.bro
- notice.bro.old
- ntp.bro
- pcap.bro
- pkt-profile.bro
- port-name.bro
- portmapper.bro



- print-filter.bro
- print-globals.bro
- print-resources.bro
- print-sig-states.bro
- profiling.bro
- reduce-memory.bro
- remote-pcap.bro
- remote-print.bro
- remote.bro
- scan.bro
- secondary-filter.bro
- signatures.bro
- signatures.bro.old
- site.bro
- smtp-relay.bro
- smtp-rewriter.bro
- smtp-rw.bif.bro
- smtp.bro
- snort.bro
- software.bro
- ssh-stepping.bro
- ssh.bro
- ssl-alerts.bro
- ssl-ciphers.bro
- ssl-errors.bro
- ssl-worm.bro
- ssl.bro
- stats.bro
- stepping.bro
- synflood.bro
- tcp.bro
- tftp.bro
- trw.bro
- udp.bro
- vlan.bro
- weird.bro
- worm.bro

## A.6 The bro/site Directory

### **signatures.sig**

*To be completed*

## A.7 The bro/logs Directory

All logs take the form

*type.hostname.start\_date/time-end\_date/time*

The date/time stamps for each record in the files are always in UNIX (ticks since epoch) format.

*type* is one of the following:

### **alarm**

Network occurrences that are determined to be of high importance will be written into the alarm file. The determination is made by the Bro policy scripts. Local site modifications can override default Bro alarms or create new ones that are site specific. Each entry contains the date/time, the alarm type, and a description of the alarm. This file is usually the "starting point" for investigation. Each alarm should be evaluated for further follow-up action.

### **conn**

All network connections detected by Bro are recorded in this file. A connection is defined by an initial packet that attempts to set up a session and all subsequent packets that take part in the session. Initial packets that fail to set up a session are also recorded as connections and are tagged with a failure state that designates the reason for failure. Each entry contains the following data describing the connection: date/time, the duration of the connection, the local and remote ip addresses and ports, bytes transferred in each direction, the transport protocol (udp, tcp), the final state of the connection, and other information describing the connection. This file is often used in forensic analysis to determine network activity by a suspect host beyond the immediate alarm.

### **ftp**

All transactions involving the well known ftp control port (21) are recorded into this file. Each entry is marked by an arbitrary session number, allowing full ftp control sessions to be reconstructed. Each entry contains the date/time, a session number, and ftp connection information or the specific ftp commands transferred. This file is often used to examine details of suspect ftp sessions.

### **http**

All transaction involving the well known http ports (80, 8000, 8080) are recorded into this file. Each entry is marked by an arbitrary session number, allowing the full http session to be reconstructed. Each entry contains the date/time, a session number, and http connection information or the specific http commands transferred. This file is often used to examine details of suspect web sessions.

## **info**

This file contains information concerning the operation of Bro during the time interval covered by the file. The entries will consist of the Bro version number, startup information, and Bro runtime warnings and errors. This file is helpful in troubleshooting Bro operational difficulties.

## **notice**

Network occurrences that are determined to be of nominal importance will be written into the notice file. The determination is made by the Bro policy scripts. Local site modifications can override default Bro alarms or create new ones that are site specific. The notice files are similar to the alarm files, but of lesser importance. Each entry contains the date/time, a notice type, a notice action, the local and remote ip addresses and ports. Optionally, depending on the type of notice, an entry might contain information about user, filename, method, URL, and other messages. This file alerts to occurrences that are worth noting, but do not warrant an alarm.

## **signatures**

This file contains information associated with specific signature matches. These matches do not necessarily correspond to all alarms or notices, only to those that are triggered by a signature. Each entry contains the date/time, a description of the signature, the local and remote ip addresses and ports, the signature id number (if available), a description of the signature trigger, a portion of the offending payload data, a count of that particular signature, and a count of the number of involved hosts. This file gives details that are helpful in evaluating if an event triggered by a signature match is a false- positive.

## **smtp**

All transactions involving the well known smtp port (25) are recorded into this file. Each entry is marked by an arbitrary session number, allowing full smtp sessions to be reconstructed. Each entry contains the date/time, a session number, and smtp connection information or the specific smtp commands transferred. This file is often used to examine details of suspect mail sessions.

## **software**

This file is a record of all unique host/software pairs detected by Bro during the time interval covered by the file. Each entry in the file contains the date/time, the ip address of the host, and information about the software detected. This file can be useful for cataloging network software. However, population of this file on a busy network often results in a huge number of entries. Since the relative daily usefulness of the file usually does not warrant the disk space it consumes, the software file is turned off by default. It can be turned on by <<<instructions>>>

## **weird**

Network events that are unusual or exceptional are recorded in this file. A number of these events "shouldn't" or even "can't" happen according to accepted protocol definitions, yet they do. Each entry in the file contains the date/time, the local and remote ip addresses and ports, and a short description of the weird activity. This file is useful for detecting odd

behavior that might normally "fly under the radar" and also for getting a general sense of the amount of "garbage" that is on the network.

### **worm**

Bro's worm.bro policy detects patterns generated by specific worms and records the instance in this file. Currently, the worms detected are code red1, code red2, nimda, and slammer. Each entry in the file contains the date/time, the worm detected, and the source ip address of the worm. This file is useful for spotting hosts that have been infected with worms.

Other files in the /logs directory are:

### **.state**

*To be completed*

### **active\_log**

*To be completed*

## **A.8 The bro/archive Directory**

The archive directory is initially empty. The script bro/script/bro-log-compress.sh populates the archive directory with compressed log files.

## **A.9 Other Files**

# Index

•  
 .state ..... 54

## A

active\_log ..... 54  
 Add a New Signature ..... 39  
 adtrace executable ..... 47  
 alarm ..... 15  
 alarm log ..... 54  
 alert\_scores ..... 48  
 autorestart file ..... 49

## B

bro executable ..... 47  
 Bro Policy Tuning ..... 44  
 bro-config script ..... 49  
 bro-logchk.pl script ..... 49  
 bro.cfg ..... 9  
 bro.cfg file ..... 48  
 bro.cfg.example file ..... 48  
 bro.rc ..... 14  
 bro.rc file ..... 48  
 bro.rc-hooks.sh file ..... 48  
 bro/archive Directory ..... 56  
 bro/bin Directory ..... 47  
 bro/etc Directory ..... 48  
 bro/logs Directory ..... 54  
 bro/pm Directory ..... 49  
 bro/policy Directory ..... 50  
 bro/scripts Directory ..... 49  
 bro/scripts/pm Directory ..... 49  
 bro/site Directory ..... 54  
 bro/var Directory ..... 49  
 bro\_config ..... 9  
 bro\_generate\_report ..... 14  
 bro\_log\_compress ..... 14  
 bro\_log\_compress.sh script ..... 49  
 Bulk Traces ..... 45

## C

cf executable ..... 47  
 check\_disk ..... 14  
 Configuration instructions ..... 13  
 conn log ..... 54  
 connection, history ..... 15  
 connection, successful ..... 15  
 connection, unsuccessful ..... 15  
 Customizing Notice Actions ..... 37  
 Customizing Policy Files ..... 33

## D

directory structure ..... 47  
 download ..... 8  
 download new Signatures ..... 39

## E

e-mail reports ..... 15  
 Editing Existing Signatures ..... 39  
 Email list ..... 3  
 external report ..... 15

## F

FAQ ..... 3  
 ftp log ..... 54

## G

PGP ..... 11, 12

## H

Hardware requirements ..... 5  
 Hardware Tuning ..... 43  
 host-grep script ..... 49  
 host-to-addr script ..... 49  
 http log ..... 54

## I

Importing Snort Signatures ..... 39  
 incident ..... 15  
 incident type ..... 15  
 info log ..... 54  
 Installation instructions ..... 8  
 internal report ..... 15  
 ip-grep script ..... 49

## M

managing disk space ..... 14

## N

Network Intrusion Detection System ..... 2  
 network tap ..... 5  
 notice log ..... 54

## O

Off-line Analysis ..... 45  
 OS Tuning ..... 43

**P**

pid file .....	49
Predefined Bro Notices .....	35

**R**

report generate, separate host .....	12
report period .....	15
rst executable .....	47

**S**

s2b-addendum-sigs.sig .....	54
s2b-functions.bro .....	54
s2b-sigaction.bro .....	54
s2b.sig .....	54
Scan Thresholds .....	40
scan, definition .....	15
scans .....	15
scans, successful .....	15
signature_scores .....	48
Signatures .....	38
signatures log .....	54
site-report.pl script .....	49
smtp log .....	54
Snort .....	3

software log .....	54
Software requirements .....	5
start_time file .....	49
starting Bro .....	14
system statistics .....	15

**T**

Terminating a connection .....	42
traffic statistics .....	15
Tuning Scan Detection .....	39
Turning Signatures ON/OFF .....	38
tutorial .....	3

**U**

Updating Router ACL .....	42
---------------------------	----

**V**

VERSION file .....	48
--------------------	----

**W**

weird log .....	54
worm log .....	54